

OKO

DATA SHEET QUAD/ATV

FUNCTION & USE

A unique sealant that has the strength to seal Off Road punctures, and also to cope with the friction and heat of racing and On Road Quads/ ATVs.

Prevents punctures of up to 7mm diameter in tubeless Quad/ ATV tyres (4mm in inner tubes) and stops tyre deflation as you drive: seals a hole in the tread area. Reduces tyre temperature and lessens the loss of air.

This product normally lasts for the legal life of a Quad's tyres. Only a small amount is used in making each seal. The rest remains liquid inside the tyre even after multiple sealing events.



APPLICATIONS

OKO works best in tubeless pneumatic tyres: inner tubes are weak and can be torn.

In race use and on bad terrain generally, it allows you to reduce pressure for maximum traction.

It was tested successfully by the Polaris France works team, who won races using OKO Quad/ATV.

BENEFITS

Tyre life extension: By keeping air in the tyre, and cooling and conditioning it from inside, OKO extends tyre life by 20% on average.

Safety: Eliminates the insecurity and danger of a puncture at speed: even if the damage is severe, it allows you to slow to a stop.

Security: Reduces the risk of being stuck deep in the country, or losing a race due to a puncture.

Economy: Lowers puncture repair/replacement costs.

CHARACTERISTICS

An aqueous glycol based solution comprising specially treated constituents of the highest grade, environmentally – friendly rust inhibitors for anticorrosion purposes, adhesion agents, gums and preservatives, held in suspension to provide a carefully engineered matrix. No shaking is necessary (unlike many other sealants that separate in the bottle and in the tyre). Cleans away with water.

Non Corrosive - Non Flammable - Non Hazardous - No adverse affect upon tyres, steel or alloy wheel rims (do not use on chrome rims which are weak and can be affected by any chemical).

Product - Reddish-pink colour. Semi-viscous. Low odour.

Quantity - Refer to bottle, drum label or www.oko.com

AVAILABLE IN:

1250ml Bottles (12 per carton)

For individual users (cap contains valve core remover and filling tube).

25 Litre Drums (32 per pallet)

For Workshop Fitment.

OKO Sealant Tariff Number:

HS 3824 90 96 (3824 90 96 99, non-EU)

Sold separately: An adjustable, all-alloy OKO Pump fits the drum and applies pre-measured OKO at up to 250ml per downward stroke, against up to 60 psi/4.1 bar tyre pressure.

OKO Pressure Application Pump Tariff Number:

HS 8413 20 00 (8413 20 00 00, non-EU)



PRECAUTIONS

Keep out of the reach of children. Wear eye protection. Do not swallow.

No specific risk and safety labels or warnings are required since this product is not classified as hazardous under current regulations. (MSDS available on request).

