

Our Professional Portfolio

**New packaging design:
Same Silotite quality in a
convenient sleeve for less waste**

Our professional range of products have a longer film length and allow for more bales per reel compared to Silotite Original 25µm, 1500m film. This results in:

- Reduced transportation costs
- Less required storage space
- Less film to recycle
- Fewer reel changes, saving valuable time



® SILOTITE Pro 1800

More bales and mixed usage.

SilotitePro1800 offers farmers and contractors several benefits including more bales per reel and time savings.

Perfect balance
between strength
and efficiency



20% more bales
per reel*



Ideal for mixed use
(round bales and
small square bales)



Available as
Sustane with
25% PCR



® SILOTITE Pro 2000

Maximum bales, less waste, fewer stops.

SilotitePro2000 is designed for maximum efficiency, with the highest potential bale output in the Silotite range.

Most efficient
SilotitePro solution



33% more bales
per reel*



Ideal for round
baler-wrapper
combi machines




Perfect pairing
with Baletite
(for Film&Film)



Width (mm)	Thickness (µm)	Length (m)	Packaging	Colours Available**
750	20	2000	Sleeve	● ● ●
750	23	1800	Sleeve	● ● ●

*Compared to Silotite Original 25µm, 1500m film. **Colours may vary according to region



® **BALETITE**

Less silage losses*



Easy opening*



Simplified recycling*



For Silage.

Baletite has been created for baling machines that can apply film instead of net. Baletite provides extra layers of protection and creates an extra oxygen barrier where it matters most, resulting in less white mould growth and fewer silage losses.

Width (mm)	Thickness (µm)	Length (m)	Reel Weight (kg)	Reels Per Pallet (#)
Edge-to-edge Coverage				
1280	16	2000	40	20
Over-edge Coverage				
1380	16	2000	43	20
1330**	15	3000	58	16

**Product range varies according to region



Up to 258 bales per reel
More baling, less stopping†

For Haylage and Stemmy Crops.

This Baletite is specifically designed for stemmy crops, higher dry matter contents and more challenging conditions. The film enables hassle free application, with a high strength and tear resistance for optimal feed preservation.

Width (mm)	Thickness (µm)	Length (m)	Reel Weight (kg)	Reels Per Pallet (#)
Edge-to-edge Coverage				
1280**	20	1650	41	20
Over-edge Coverage				
1380	20	1650	45	20

**UV Protected – Recommended option for single balers



*Compared to netwrap. †Compared to Baletite 2000m, 16µm.