

ST54™

ENHANCED MULTI-MISSION
TACTICAL OPERATOR SCBA



Self-Contained Breathing Apparatus

AVON
PROTECTION

ST54™

ENHANCED MULTI-MISSION
TACTICAL OPERATOR SCBA



Avon's state-of-the-art ST54™ Tactical Operator SCBA has been developed specifically for tactical officer and technician applications where the operator needs to respond to ever changing operational conditions.

The ST54 SCBA is the base to a multi-mission Respiratory Protection System that provides operational flexibility to operators and mission commanders in the field for a tailored PPE response based on available intelligence. Depending on the threat or operational situation at the scene of an incident, the ST54 SCBA can be configured to provide the appropriate protection.

The ST54 SCBA combines Avon Protection Systems' M53A1™, FM53™ and FM54™ respirators (see respirator datasheets for further details) with new and innovative modular breathing apparatus technology to provide positive pressure SCBA and/or PAPR capability. The ST54 system provides the operator with total flexibility to select the necessary level of protection quickly and efficiently without degradation of operational effectiveness. Designed with the tactical mission in mind, the system incorporates non-reflective black components and warning whistle which can be silenced.



FM53™ | M53A1™



FM54™

- Available in 4 sizes for custom fit for all operators
- 5 interchangeable silicone nose cups for improved comfort and performance
- Comfortable reflex seal with low profile brow for helmet compatibility

Cylinders

The ST54 two-piece clamshell composite backframe accommodates a variety of 4500 psi carbon cylinders in durations of 30, 45 or 60 minutes, as well as a 5500 psi carbon cylinder in a 70-minute duration. Both natural and stealth black cylinder finishes are available along with optional stealth cylinder bag covers. A quick release universal cylinder band allows for fast and easy cylinder exchange.

End of Service Time Indicators (EOSTI)

The ST54 backframe includes a remotely accessible, chest mounted pressure gauge (available with stealth black and luminescent face options) for monitoring of cylinder pressure and an end-of-service whistle alarm that can be disabled if required.

Compact Demand Valve (CDV)

The world's smallest, most compact chemically hardened demand valve provides constant positive pressure. With the option to mount on either side of the respirator, the CDV is unobtrusive and allows excellent integration with weapons and other tactical gear. The CDV is attached to the respirator via a standard 40mm thread connection.

AVON CS-PAPR™

COMBINATION SYSTEM POWERED
AIR PURIFYING RESPIRATOR



The Avon CS-PAPR™ is the newest generation of CBRN Powered Air Purifying Respirator (PAPR) designed for use in Combination Unit Respirators (CUR). The capability to change levels of protection dependent on the threat now provides the wearer with increased duration on target and safer operation.

Utilizing the Avon MP-PAPR™ module along with the patented combination hose module, the wearer can seamlessly switch between APR, PAPR and SCBA modes of protection. The single air hose connection for all modes allows the operator to retain a clear mask cheek for optimum weapon sighting.

Optional Auto Filter Covers limit exposure of CBRN canisters to IDLH or unknown atmospheres when in SCBA mode.

APR
PAPR
SCBA



ACCESSORIES/OPTIONS

SCBA

- Rapid Intervention Crew (RIC) fitting located at the cylinder valve allows for emergency filling of a cylinder in operation
- Remote Lightning Fill™ located on the right shoulder strap allows rapid cylinder filling by a single operator to extend mission time
- Universal Emergency Breathing Safety System (UEBSS) located on the left side of the waist belt allows the ST54 user to connect to another ST54 to share cylinder air for immediate egress without disconnecting in an IDLH atmosphere

RESPIRATOR

- Hydration systems including traditional canteen and bladder systems
- Vision correction system supporting +8 to -10 diopter
- Quick attach outserts: clear, sunlight, blue blocker, laser, mirrored and shade-5
- Range of stowage carriers

COMMUNICATIONS




- Next generation voice projection unit (VPU)/amplifier with internal waterproof microphone assembly
- 3-pin electronic communications port (ECP) for radio interface

FILTER/CANISTER OPTIONS

- Respirator options include unique conformed close fitting filter/canister design, providing the operator with greater visibility and improved weapon sighting and ergonomics
- NIOSH approved options include the CBRNCF50 (CBRN) and CTCF50 (Riot Agent)
- MIL-SPEC options include General Purpose (GP) filter and CS/CN filter

Breathing Performance SCBA Mode			Breathing Performance PAPR Mode				
Breathing Rate	40 lpm		Breathing Rate	120-130 lpm			
Environmental Range	-15°F to +140°F (-26°C to +60°C)						
End Of Cylinder Air	Able to sustain positive pressure down to 10 Bar (145 psi) cylinder pressure						
Breathing Performance in APR Mode							
Breathing Resistance			Exhalation breathing resistance of no greater than 20mm of water at 85 lpm in a negative pressure mode				
Inhalation Resistance Including Canister			50mm of water at 85 lpm				
Live Agent Performance							
Challenge Chemical	Requirements		Actual		Test Agent	NIOSH CBRN Requirements	Typical Performance
	Max Peak (mg/m ³)	Max Cumulative (mg-min/m ³)	Max Peak (mg/m ³)	Max Cumulative (mg-min/m ³)			
Sarin (GB)	0.600	6	0.004	0.203	Sarin (GB)	6 Hours	> 6 Hours
Mustard (HD)	0.087	6	0.005	0.800	Mustard (HD)	6 Hours	> 6 Hours
Material Used							
53/54 Series Masks			Chlorobutyl / silicone rubber and polyurethane visor				
Harness			Kevlar webbing with stainless steel and nylon hardware				
Back Plate			Radel® PPSU (Polyphenylsulfone) thermoplastic				
Cylinder Valve (non-locking)			PTFE impregnated, hard anodized aluminum				
CS-PAPR			CBRN hardened butyl and PPE				

Cylinders							
Part Number	Pressure (psi)	Material	Free Air Capacity	NIOSH Rated Duration @ 40 lpm	Cylinder & Valve Charged Weight	Cylinder Diameter	Hydrostatic Interval
124053	4500	Full wrapped carbon, black	1274 liters 45 cu. ft.	30 min.	11.0 lbs.	5.4 in.	5 years
124054			1840 liters 65 cu. ft.	45 min.	14.8 lbs.	6.3 in.	
124055			2462 liters 88 cu. ft.	60 min.	19.2 lbs.	6.9 in.	
124028	4500	Full wrapped carbon, natural	1274 liters 45 cu. ft.	30 min.	11.0 lbs.	5.4 in.	
124029			1840 liters 65 cu. ft.	45 min.	14.8 lbs.	6.3 in.	
124030			2462 liters 88 cu. ft.	60 min.	19.2 lbs.	6.9 in.	
602318	5500	Full wrapped carbon, black	3113 liters 110 cu. ft.	70 min.	20.4 lbs.	7.1in.	

Certifications		
 The Avon ST54 carries a NIOSH Industrial Approval under the provisions of 42 CFR 84 TC-13F in a variety of cylinders and facepiece size combinations.	Approval Number	Description
	TC-13F-0955	30 MIN 4500 PSIG
	TC-13F-0956	45 MIN 4500 PSIG
	TC-13F-0957	60 MIN 4500 PSIG
	TC-13F-0958	70 MIN 5500 PSIG

The Americas

t: +1 888 286 6440

e: customerservice@avon-protection.com

Europe, Middle East, Asia, Africa & Australasia

t: +44 (0) 1225 896705

e: protection@avon-protection.com

avon-protection.com



GR03833-01 Copyright © 2021 Avon Protection. All rights reserved.



avon-protection.com

