

VES-D1301

Features

- 1920 x 1080 Resolution
- 5 Point Capacitive Touch
- 1000 cd/ m² Brightness
- IP 65 Front Panel
- Support VESA mount

Specifications



| | |
|------------------------------|--|
| Size | 13.3-inch |
| Resolution | 1920 x 1080 |
| Aspect Ratio | 16:9 |
| Backlight | LED |
| Brightness | 50~1000 nits (Auto Dimming adjustable) |
| Contrast Ratio | 900:1 |
| Display Color | 16.7M |
| Response Time | 40ms (max) |
| Viewing Angle | 85°/85°/85°/85° (R/L/U/D) CF>10 |
| Active Area | 293.76 x 165.24 mm |
| Interface | HDMI x 1, VGA x 1, USB type B x 1, USB type A x 2, USB type C x 1, 3.5mm AUX audio Line out x 1 |
| Glass | Anti-Glare, Anti-Reflective |
| Touch Interface | USB type B |
| Power Input | 11V ~ 16V, 5A (12V nominal) |
| Power Adapter | 12V 5A (Optional) |
| Operating Temperature | -20 ~ 70 °C |
| Storage Temperature | -30 ~ 80 °C |
| Waterproof | IP65 Front Panel |
| Spark | 5Wx2 |
| Weight | 3.5Kg (max) |
| Dimension(mm) | 349.09 x 252.24 x 32.4 mm |
| Mounting | 75 mm VESA Mount |
| Certification | CE, FCC Class B, Safety EN60950 |
| Compliance | MIL-STD 810G shock and vibration specifications MIL-STD 810G Temperature and Humidity (operational and storage) |
| Accessories | HDMI Cable x 1, USB type B Cable x1, VESA Mounting Screws x 4 (All in accessories bag), Power Cable x1 |