

## Model Nomenclature

### IWOS Line Sensor

Overhead Line Sensor Model	Model code: IWO-C-<C/E/U/M><5/6><A/L>		
	<C/E/U/M>: Short-range Frequency	<5/6>: Line Frequency	<A/L>: Version
IWO-C-<C/E/U/M><5/6><A/L>	C: 470-510MHz E: 433.05-434.79 MHz U: 915-928MHz M: 866MHz	5: 50Hz 6: 60Hz	A: AI - 1A Power Harvesting L: LT - 2A Power Harvesting
Example:	IWO-C-C6A: overhead line sensor, short-range communication frequency is 470-510MHz, applicable to 60Hz 10KV power lines.		

### IWOS Concentrator - Pole-mounted / Line-mounted

Concentrator Model	Model code: IWO-HD/HX-<WMNN>-<C/U/M/E><5/6><A/B/C/D/E/F><2/3/N>				
	<WMNN>: Cellular Type & Module	<C/U/M/E>: Short-range Frequency	<5/6>: Line Frequency	<A/B/C/D/E/F>: Battery	<2/3/N>: Solar Power
IWO-HD/HX-<TL00>-<C/U/M/E><5/6><A/B/C/D/E/F><2/3/N>	China - LTE CAT4: LTE-FDD B1/B3/B5/B8 LTE-TDD B38/B39/B40/B41 TD-SCDMA B34/B39 UMTS(DC-HSPA+) B1/B5 GSM: B2/B3/B5/B8				
IWO-HD/HX-<LQ25>-<C/U/M/E><5/6><A/B/C/D/E/F><2/3/N>	Europe, Middle East, Africa, South Korea, Thailand, India - LTE CAT4: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 GSM: B3/B8				
IWO-HD/HX-<FQ78>-<C/U/M/E><5/6><A/B/C/D/E/F><2/3/N>	Australia, New Zealand, Taiwan, Latin America - LTE CAT4: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8 GSM: B2/B3/B5/B8	C: 470-510MHz U: 915-928MHz M: 863-868MHz E: 433.05-434.79MHz	5: 50Hz 6: 60Hz	A: 7.2Ah Lead-acid B: 12Ah Lead-acid C: 40Ah Li-phosphate D: 40Ah Gel E: 12Ah Li-phosphate F: 3.3Ah Li-phosphate	2: 20W 3: 30W N: No solar power
IWO-HD/HX-<FQ13>-<C/U/M/E><5/6><A/B/C/D/E/F><2/3/N>	North America, AT&T, T-Mobile - LTE CAT1: LTE-FDD Band2/4/12				
IWO-HD/HX-<FQ58>-<C/U/M/E><5/6><A/B/C/D/E/F><2/3/N>	EMEA, South Korea, Thailand, India- LTE CAT4: LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8				
Example:	IWO-HD-LQ25-C5B2: Concentrator, pole-mounted, supports Europe and Asia Pacific networks, short-range communication frequency is 470-510MHz, applicable to 50Hz 10KV power lines, packaged with 12Ah lead-acid battery, 20W solar panel.				

# AI-enabled Preventive Grid Analytics



Fault Detection & Location



Preventive Analysis



Lower Maintenance Costs



Improved Grid Reliability and Safety



# IWOS: Line Sensor + Concentrator + AI Analytics Platform

## System Components

### Line Sensor

- + Compatible with **50/60Hz** grids
- + High precision current measurement: **0~630A, ±0.5%**
- + High sampling rate of oscillography waveforms: **12.8/15.36kHz** (256 samples/cycle)
- + Zero-sequence current synthesis enabled by **10µs** precision sync
- + Power optimization operation
  - Full-function mode: all functions including waveform recording enabled; powered by line and supercapacitor
  - Low-power mode: waveform recording disabled; powered by line and battery
- + Power harvesting: **1A** to support full-function mode; supercapacitor backs for 12h
- + IP67, water proof
- + Light weight: <1.5kg, live installation and removal

### Concentrator

- + WAN: **LTE**
- + Field Area Network: Sub-1G short range radio
- + High-Precision (1µs) GPS for location and time synchronization
- + Fault detection based on zero-sequence current synthesis
- + Main and backup power: Line harvesting (solar), maintenance-free capacitor
- + IP67(IP55) protection
- + Remote upgrade & maintenance

### AI Analytics Platform

- + Sensor and concentrator management
- + GIS-based real-time monitoring of line status and events
- + Deep learning analytic system
  - Oscillography waveform classification powered by **AI algorithms**
  - Accurate fault location and Email/SMS/Mobile APP alarms
  - **Preventive analysis** and early warning
- + **Flow Direction & Load Analysis**
- + Reports
  - Load trend & statistics
  - Power quality analysis
  - Fault statistics

Installed equipment	Covered line	Covered substation	Collected Fault recording data	Detected Line failure
<b>150,000+</b>	<b>32,000+</b>	<b>3,500+</b>	<b>100 Million+</b>	<b>110,000+</b>

