

17 July 2024

HydroVision International

S M Shafiul Alam

Demonstrating Black Start and Islanded Operation of a Small Hydropower Plant*

***National laboratory contributions were funded by the U.S. Department of Energy's Water Power Technologies Office as part of the HydroWIRES Initiative**

Presentation prepared by Battelle Energy Alliance, LLC under Contract No. DE-AC07-05ID14517 with the U.S. Department of Energy.

INL/MIS-21-65075, INL/CON-22-70130, INL/CON-23-74996




Disclaimer

DISCLAIMER


This information was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trade mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Government or any agency thereof.

Hydropower in the US (as of 2016)



Source: National Hydropower Asset Assessment Program FY15 Plant Database [15]


Figure 2-8. Distribution of operating modes for hydropower facilities, by number of projects



Source: National Hydropower Asset Assessment Program FY15 Plant Database [15]

Figure 2-9. Distribution of operating modes for hydropower facilities, by capacity


US Small Hydro (<10MW) Fleet




- Can small hydropower form microgrid during
 - Public safety power shutoff?
 - Load-shed in the winter?
 - Bulk grid black out?

Black Start and Restoration

Top-Down Restoration with a high-voltage transmission system






Bottom-Up Restoration with a distribution system



➔ Cranking path & power
➔ Restoration power flow
● ● Restoration sequence


➔ Cranking path & power
➔ Restoration power flow
● ● Restoration sequence
 Islanded system

Islanded Distribution Grid Black Start: Successful Field Demonstration with Idaho Falls Power



2nd Field Demonstration: Black Start Felt Plant

- Utility: Fall River Rural Electric (FRE) Cooperative.
- Remote site.
- Minimal retrofit to exiting flow control.
- Mobile energy storage support with automatic control.



Interconnection




Felt plant

Badger Substation

Satellite Image Source: Google Maps

Winter Transportation: From Badger substation to Felt Plant (0.8 miles)





Black start Felt plant and support the Teton basin critical loads over the 46kV line

Image Source:
US Energy Information Administration

Steps to De-risk the Field Demonstration

Modeling

- Collect hydrogovernor data in grid connected mode of operation
- Develop hydrogovernor model for ROR hydropower on Simulink

Simulation

- Set hydrogovernor in islanded mode
- Analyze response to load step change on Simulink
 - Without Storage
 - With Storage

Test


- Develop RSCAD model for digital real-time simulation (DRTS)
- Conduct power hardware-in-the-loop (PHIL) test

Felt Plant Technical Information

- Number of units: 2
- **Turbine: Francis**
- Rated head: 155 ft, maximum head: 156 ft, minimum head: 154 ft.
- Combined generation capacity of 2 units: 5.5 MW (156 ft head); 5.43 MW (154 ft head)
- Combined design flow rate for two units: 500 CFS, minimum: 125 CFS
- **Rated combined capacity of the two turbines: 2 x 3840 HP = 5.73 MW**
- Penstock length: 1750 ft
- Penstock diameter: 8ft
- Synchronous Speed: 600 RPM
- **Inertia constant of one unit (calculated): 2.264 sec**
- **Recommended Tw for testing: 0.75 ~ 1.5 sec**
- Power versus gate curve has been obtained through onsite test.

Information Source: FERC#5089, 08/31/2021; Tests performed by Mercury Governor, and FRE plant photo shoot.


PHIL Test Set Up



Felt Plant Transients with RAPID MIB

Islanded Felt Plant: 0 MW --> 0.1 MW


Without MiBox With MiBox



100 kW → 75 kW

freqFelt


Frequency Overshoot




100 kW → 75 kW

I RMS

Active Power Absorption



Felt Plant Existing Control



HPU: Hydraulic Power Unit

PLC: Programmable Logic Controller

SCADA: Supervisory Control and Data Acquisition

Guide Vane: Wicket Gate for Francis Turbine

Digital Governor Retrofit

- Installed PLC for each unit and interfaced start/stop sequence with existing wiring.
- Replaced existing simple open/close directional valve with proportional valve.
- Added a guide vane / gate position linear transducer.
- Added a generator PT speed sensing module.

Bypassed SCADA


HPU: Hydraulic Power Unit

PLC: Programmable Logic Controller


SCADA: Supervisory Control and Data Acquisition

Guide Vane: Wicket Gate for Francis Turbine

INL/MIS-23-74613



a) PLCs are installed for each unit



Cable retrofit for feedback and actuation

b) Proportional valve replaces directional valve

- Grey cable sends actuation signal from PLC.



Existing directional control valve



New proportional valve


c) Gate position transducer is installed

- Orange cable sends position back to PLC.




Hydraulic Tuning

Felt Plant Unit 1 Hydraulic Tuning, 07/14/2023




Felt Plant Unit 2 Hydraulic Tuning, 07/17/2023




Gate Opening and Closing Timing

Felt Plant Unit 2 Open Timing, 07/17/2023



0 – 100% Gate opening time: 22 sec

Felt Plant Unit 2 Close Timing, 07/17/2023




0 – 100% Gate closing time: 25 sec


Response time before retrofit: 3~4 minutes

Startup to Breaker Closer

Felt Plant Unit 1 Startup To Breaker Closer, 07/18/2023





Felt Plant Unit 2 Startup To Breaker Closer, 07/17/2023



Oscillation goes away as soon as grid connected

Unit 1 Operation on 19th July 2023

Felt Plant Unit 1 Isolated, 07/19/2023



Isolated mode carries station load (10% of unit capacity). Oscillation (of range: 0.6 Hz) is present in Isolated Mode – Direct consequence of low loading and vacuum pressure valve reaction.

Gate position responses in hysteresis fashion.

Lessons from FRE Demonstration

- Guide vane control
 - Minimal retrofit can enable smoother and high-resolution control.
- Connecting a “traditionally grid following” small hydropower plant to “dead” grid,
 - Need to assess auxiliary power system.
 - Need to audit contact switches.
 - Need to have “islanded” mode protection settings.
- Inverter operating mode will vary based on energy storage siting,
 - Grid following would be better near the hydropower plant.
 - Grid-forming would be better near the critical loads.

Ongoing Effort

- Black start Implementation Guidance is under development
 - How to enable black start of a traditionally Non-black start Hydropower Plant or grid dependent hydro (GDH) ?
- INL is working with some case study partners for the validation of this Guidance
 - No cost share
 - Not a field demonstration
 - INL Announcement Link: <https://inl.gov/news-release/idaho-national-laboratory-seeks-small-hydropower-utility-for-case-study/>

References

Black Start Field Demonstration with FRE

1. Ojo et al. 2024 “Frequency Response Improvement in a Standalone Small Hydropower Plant Using Battery Storage”, DOI: <https://doi.org/10.1109/TEC.2024.3416998>
2. Gilbert et al. 2024 “High-Penetration Microgrids Providing Grid Stability Using Frequency-Watt Control”, DOI: <https://doi.org/10.1109/GreenTech58819.2024.10520610>
3. INL Article on FRE Demonstration, 2023: <https://inl.gov/water-power/new-tech-brings-resilience-to-small-town-hydropower/>
4. INL Article on RAPID MIB, 2023: <https://inl.gov/integrated-energy/microgrid-in-a-box-opening-new-possibilities-in-defense-utilities-disaster-relief/>
5. Ojo et al. 2023 “Black start demonstrations of small hydropower plants with energy storage”, Link: <https://www.osti.gov/servlets/purl/2203558>

Black Start Field Demonstration with IFP

1. Alam et al. 2022 “PHIL Validation of Ultracapacitor Storage for Black Start Application”, Link: <https://www.osti.gov/servlets/purl/1906486>
2. Alam et al. 2022 “Power Hardware-In-the-Loop Hydropower and Ultracapacitor Hybrid Testbed”, DOI: <https://doi.org/10.1109/PESGM48719.2022.9917167>
3. Alam et al. 2022 “Enhancing Local Grid Resilience with Small Hydropower Hybrids: Proving the concept through demonstration, simulation, and analysis with Idaho Falls Power”, INL/RPT-22-69038. DOI: <https://doi.org/10.2172/1891110>
4. Banerjee et al. 2022 “Modeling a Bulb-Style Kaplan Unit Hydrogovernor and Turbine in Mathworks-Simulink and RTDS-RSCAD”, DOI: <https://doi.org/10.1109/TD43745.2022.9816952>
5. Alam et al. 2021 “Idaho Falls Power Black Start Field Demonstration - Preliminary Outcomes Report”, INL/EXT-21-63855. DOI: <https://doi.org/10.2172/1817907>

Thank You!

S M Shafiul Alam
SMShafiul.Alam@inl.gov



Yemi Ojo
Hill Balliet
Jeremiah Gilbert
Porter J. Hill
Kurt S. Myers
Joey Glines
Nicholas P. Smith



Weihang Yan
Vahan Gevorgian

MERCURY GOVERNOR

Greg Yohe



Chad Johnson
Dave Peterson