



The Multi E-Launcher has been designed for pedestrian, misuse and component impact test. The system includes a state of the art E-launcher, controlled by electrical linear motors technology.

There are many advantages to the user:

- Better control and, therefore, much better impact speed accuracy
- Higher repeatability, as system is less influenced by external factors
- Lower acceleration during the propulsion, protecting impact shapes from high force peaks
- Clean and maintenance free
- Silent operation: less acoustic noise
- Compact design: less occupied space
- No need of pre-tests






- ✓ PEDESTRIAN: ECE R127, European Directive 78/2009, 631/2009, EEVC - WG17, GTR N° 9, Euro NCAP, JNCAP, KNCAP, U.S. NCAP, C-NCAP, ANCAP, Japan Article 18 A99, AIS 100, GB 24550
- ✓ GUIDED HEAD: ECE R12, FMVSS 201/203, GB 11557
- ✓ BODY BLOCK: ECE R12, FMVSS 203, GB 11557
- ✓ HEAD FORM PENDULUM: ECE R21, FMVSS 201/202A, ECE R17, ECE R25, ECE R80, TRIAS 20, GB 11552
- ✓ FREE MOTION HEAD FORM (FMH): FMVSS 201U
- ✓ EJECTION MITIGATION: FMVSS 226
- ✓ AIRBAG TEST
- ✓ MISUSE TEST



E-Launcher

Controlled by Electrical Linear Motors Technology





- Compact design
- Controlled by electrical linear motors technology
- Speed accuracy: better than $\pm 0,05$ km/h
- Maximum speed: 61 km/h*
- Maximum propelled mass: 50 kg* (free flight), 130 kg* (guided)

* Others under request

Positioning and Support Frame: (other ranges under request)

- ## Automatic Recovering Device:

A red overhead crane system is shown lifting a large, complex industrial machine. The crane has a red frame with a horizontal beam supported by two vertical legs. A blue hoist is suspended from the beam, and a cable is attached to the machine. The machine is red and white, with various components and a control panel. The crane is positioned over a concrete floor, and the machine is being lifted from a platform.

- Pedestrian legforms: aPLI, FlexPLI, TRL
- Pedestrian headforms
- Body block
- Misuse: PDI-2, ...

ADDED value Passive Safety Test Systems

www.additium.com
Loeches 66, N-4
28925, Madrid, SPAIN
info@additium.com
Phone: +34 910 612 763

