POWERSPORT
PERFORMANCE PRODUCTS

AEROSOLS & CLEANERS



Silicone Detailer
AEROSOL SPRAY
2916 13 fl oz / 385 mL
- Restores shine to plastics, vinyl, and rubber.
- Resists dirt and dust for a lasting clean.
- Safe on all powersports and automotive surfaces.



Chain Lubricant
AEROSOL SPRAY
2915 13 fl oz / 385 mL
- Clear, no-sling formula.
- Designed to repel, and not collect dirt.
- Perfect for on-road and off-road use.



Foam Filter Oil
AEROSOL SPRAY
2917 13 fl oz / 385 mL
- Super tacky formula traps dirt and particulates.
- Maximizes airflow.
- Water-resistant, will not gum or clog the filter.



Brake Parts Cleaner
AEROSOL SPRAY
2918 14 fl oz / 414 mL
- Non-chlorinated formula that dries quickly.
- Leaves no residue after cleaning.
- Powerful spray removes grease and oil.



PowerWash® Moto Formula
SPRAY CLEANER
M10025 32 fl oz / 946 mL
- Quickly dissolves dirt, mud, and grime.
- Removes tough stains without streaking.
- Safe for all powersports and automotive surfaces.



Power T.A.R. Remover®
RUBBER REMOVER
2125 17 oz / 502 mL
- Removes rubber, adhesives, tar, and oil-based grime.
- Safe on paint, vinyl wraps, graphics, and Lexan.
- Biodegradable formula that cleans tough residues.

VPRacingFuels.com



PN9410_PS_26 (II26) ©VP Racing Fuels, Inc.

POWERSPORT
PERFORMANCE PRODUCTS

SCAN HERE

POWERSPORT FUELS

VP Racing fuels are formulated using the highest quality base stocks and components available. They are produced in the United States with uncompromising attention to consistency and control to deliver maximum performance with absolute precision.



FUELS	Size	Part Number	Oxygenated	Leaded	Unleaded	Motocross	Motorcycle Road Racing	ATV/UTV	Karts	PWC & Power Boat
C50+ REG	5 GAL / 18.9 L	1172	Y		•	•				
T2+	5 GAL / 18.9 L	2922	Y	•		•		•	•	
T2+ REG	5 GAL / 18.9 L	2432	Y	•		•		•	•	
T4+	5 GAL / 18.9 L	4312	Y		•	•	•	•	•	•
T4+ REG	5 GAL / 18.9 L	2452	Y		•	•	•	•	•	•
U4.4 REG	5 GAL / 18.9 L	2382	Y	•		•	•			
C12	5 GAL / 18.9 L	1122	N	•		•	•	•	•	•
UTV 96 REG	5 GAL / 18.9 L	2532	Y		•			•		
MR PRO 6 REG	5 GAL / 18.9 L	2332	Y		•	•		•		
VP MOTO R REG	5 GAL / 18.9 L	4112	Y		•	•	•	•		
VP MGP R REG	5 GAL / 18.9 L	4122	Y		•		•			
MRX02 REG	5 GAL / 18.9 L	2362	Y	•		•		•	•	
MR12	5 GAL / 18.9 L	6222	Y	•		•	•	•		

Most fuels and oils are available in 54 gal drums.

PERFORMANCE COOLANTS



Not an additive.

Stay Frosty® Race-Ready

PERFORMANCE COOLANT

2301 64 fl oz / 1.9 L
23051 1 gal / 3.8 L
2308 5 gal / 19 L
2254 54 gal / 204 L

- 100% water-based, glycol-free.
- Ready-to-pour coolant replacement.
- Reduces engine temps up to 30°F, head temps up to 75°F.
- Protects cooling system components from corrosion and electrolysis.
- Lubricates pumps, seals, and protects radiators.



Not an additive.

Stay Frosty® Hi-Performance

PERFORMANCE COOLANT

2087 64 fl oz / 1.9 L
23071 1 gal / 3.8 L

- Ready-to-pour coolant replacement with freeze protection to 0°F.
- Reduces engine temps up to 14°F, head temps up to 25°F.
- Protects cooling system components from corrosion and electrolysis.
- Lubricates water pumps and seals.

LUBRICANTS & ADDITIVES



4T Full Synthetic

FULL SYNTHETIC OIL

2937 10w-40 32 fl oz / 946 mL
2938* 10w-50* 32 fl oz / 946 mL
2939* 5w-50* 32 fl oz / 946 mL

- Maximum performance & protection.
- Wet clutch compatible.
- Hyper-ZDDP and anti-wear additives extend engine life.
- V-Twin Compatible.*



4T Syn. Blend

SYNTHETIC BLEND OIL

2935 10w-40 32 fl oz / 946 mL
2936* 20w-50* 32 fl oz / 946 mL

- Synthetic & conventional base oil protection.
- Wet clutch compatible.
- Outstanding anti-wear and oxidation protection.
- V-Twin Compatible.*



4T Conventional

CONVENTIONAL OIL

2948 10w-40 32 fl oz / 946 mL
2949* 20w-50* 32 fl oz / 946 mL

- Superior anti-wear technology.
- Wet clutch compatible.
- Smooth shifting with minimal clutch slippage.
- V-Twin Compatible.*



2T Full Synthetic

FULL SYNTHETIC OIL

2944 32 fl oz / 946 mL

- Full synthetic low smoke, low-ash formulation.
- Superior high-temp performance and protection.
- Engine wear protection and prevention of corrosion.



2T Syn. Blend

SYNTHETIC BLEND OIL

2943 32 fl oz / 946 mL

- Advanced protection with synthetic and conventional base oil.
- Prevention of corrosion and plug fouling.
- Protection even at higher temps.
- Low smoke formulation.



80w Gear Oil

2T/4T API GL-4 GEAR OIL

2946 32 fl oz / 946 mL

- Anti-wear additives protect critical gear components and prevent scuffing.
- Long-lasting inhibitors protect against corrosion, rust, and foaming.
- Improves shifting and reduces transmission noise.



622 Brake Fluid

DOT 4 FULL SYNTHETIC

2551 16.9 fl oz / 500 mL

- Dry boiling point of 622°F.
- Resists brake fade caused by excessive heat from high speeds or riding the brakes.
- Full synthetic for use in automobiles and powersports.



Octane Booster

GASOLINE ADDITIVE

28555 16 fl oz / 473 mL

- Increases octane up to 5 full numbers.
- Improves throttle response and acceleration.
- Eliminates knocking and pinging.