

Flexible Entertainment Lighting

FLEXIBLE ENTERTAINMENT LIGHTING PRODUCTS LONG LIFE SPAN OF PRODUCTS DRY HIRE TO SUPPORT CUSTOMERS' INVESTMENTS



www.luxibel.com

VISIT OUR NEW WEBSITE

This catalogue replaces all previous catalogues and is subjected to change without further notice. No rights can be derived from this catalogue. Luxibel® is a registered trademark of AED Distribution NV. Luxibel® - 2024 - www.luxibel.com



CRI > 95 High-power Calibrated LEE filter color bank 8 color temperature preset buttons Unique RGBWWLC LED with warm white



XPA-400C

MULTI-COLOR SOFTLIGHT

The XPA-400C is a compact but highpower RGBWWLC LED panel, ideal for applications that require a powerful but compact light. The device is equipped with an intuitive control interface, featuring a 4-button menu and an LCD display for straightforward navigation, along with an 8-button programmable manual CCT bank



and 3 versatile rotary/push buttons

for precise manual adjustments.

Additionally, it boasts a calibrated LEE filter library, incorporating over

60 popular colors. Its firmware can

be updated via USB in 10 DMX linked

devices at a time. The fixture has


9 DMX Modes, including 3 B Expo

100MWW compatibility modes.

Features



12-leaf barndoor





Honeycomb

30° and 60°



Pole operated yoke

2800K - 10000K

8 CCT preset buttons

0000

0000

Accessories

Included: 12-leaf barndoor with barndoor, medium diffuser, omega bracket, spigot, PowerCon True1 M/F Optional: pole operated yoke, intensifier, 30° and 60° honeycomb





9 modes

Low Voltage Input

(4)

USB firmware updates

405 x 129 x 418 mm

WxHxD

12,8 kg

DMX

LEE filter color bank



RGBL **CRI > 90 High-power Compatible with B EXPO100 Calibrated LEE filter color bank**



XFR-140C



MULTI-COLOR FRESNEL

The XFR-140C is a compact but powerful RGBL fresnel light with an adjustable zoom from 21° to 85° and a 4-leaf barndoor. The fixture has the capacity to go full color but is also designed to match the white color temperatures of the Luxibel B EXPO 100MWW, 200MWW and 200MCW

utilizing its 6 DMX modes. The fresnel now includes a convenient USB slot for software updates, simplifying the process for up to 10 DMX-linked fixtures simultaneously. Another of the fixture's novelties is the calibrated LEE filter library with various common colors in the industry.

Features



Optional white cover kit



4-leaf barndoor

Included: 4-leaf barndoor with safety, PowerCon True1 M/F



Manual zoom 21°-85°



OLED display



One-hand tilt locking system





LED RGBL

Accessories







LEE filter

Low Voltage Input

(4)

USB firmware updates

298 x 327 x 271 mm

WxHxD

5,48 kg

>90

CRI





FL-300TW

IP66 **CRI > 95 High-power** Strong aluminium housing 4 color temperature preset buttons





XFL-300TW 🖸 🗖 🖾 🖾

TUNEABLE WHITE FLOODLIGHT


The XFL-300TW is an IP66, high-CRI flood light with 4 preset color temperatures. It has a streamlined design that ensures easy transport and straightforward installation. These features make it the ideal fixture for many situations that require a high-quality flood light: exhibitions, festivals, venues, and architectural lighting. It's a brighter, more modern replacement for the traditional HQI 400 type floodlight that reaches full brightness immediately.

Features



Powercable in-out

 Silent, no fans High-CRI



4 color temperature preset buttons





2800K - 6000K







EU (CE), UK (UKCA)

Extremely high and stable output



60°













7,8 kg



RJ45 in/out Brackets for versatile rigging 120x 5W CW LEDS mappable per 4 120x 0.6W RGB LEDS individually mappable Supports Kling-Net, Art-Net[™], sACN and DMX



B BLAST PRO | 🏛 🙎 |

HIGH-POWER CW STROBE BAR WITH RGB PIXELS

Introducing the B BLAST PRO: a powerful and flexible IP65 strobe bar for stunning lighting effects! Equiped with 120x 5W CW and 120x 0.6W RGB LED bulbs, this eye-catcher is perfect for festivals, clubs, and stages. Its versatile locking system allows you to stack the strobe bars at any angle, horizontally or vertically, offering unparalleled flexibility. The B BLAST PRO also includes a variety of brackets. Among these is the B BRACKET PRO, which enables vertical mounting under a truss or stacking on the floor with a base plate. The shape bracket facilitates the creation of various shapes, and the tilt brackets enables tilting the fixture.

Features



Horizontal + vertical locking



Individual pixel mapping



Tilt bracket



Shape bracket for

geometric set-ups

B BRACKET PRO for vertical set-up



RJ45 in/out



Accessories

Included: Tilt, shape and omega brackets, B BRACKET PRO Optional: Frost filter white, frost filter black, floor stand



120x 0.6W LED RGB







DMX

5 modes




800W AC 100V-240V

יווווווו WYHYD 85 x 255 x 1.000 mm

10 ka

w/ tilt bracket

IP65



MULTI DOLLY

PRE-RIG, PRE-PRODUCTION AND TRANSPORT DOLLY SYSTEM

The MULTI DOLLY, presented by Luxibel is a revolutionary pre-rig, pre-production and transport dolly system. The foundation of this dolly is a galvanized frame, useable in combination with Tente wheels on the side or on the bottom. The frame can therefore be used in multiple set-ups. It can be used horizontally or vertically in combination with standard NX34 square truss, standard size, or with solo tubes.

Compatible with:

- Tente wheels
- NX34 truss
- Solo tube



DOLLY COVER

RAIN AND DUST PROTECTION FOR TRANSPORT DOLLIES

Introducing the ultimate solution to safeguard your light fixtures and equipment from dust and sand, and from unpredictable weather conditions. Its transparent design on the front and back allows for visibility, ensuring you can easily identify your gear without having to remove the cover. Two sizes are available: standard size and half size. Both feature convenient zippers that ensure quick and easy access to your equipment.

Two cover sizes available:

- 1600 x 990 x 590 mm (WxHxD)
- 1600 x 1990 x 590 mm (WxHxD): Compatible with MULTI DOLLY



www.luxibel.com

AED Distribution NV

Bedrijvenpark De Veert 13/004, 2830 Willebroek, Belgium +32 3 860 76 50 | info@luxibel.com