

Intersteller Green



SPECIFICATIONS

Engine

Type Parallel twin, 4 stroke, SOHC, Air-Oil Cooled

Displacement 648cc

Bore x stroke 78 mm x 67.8 mm

Compression Ratio 9.5:1

Maximum Power 34.6 kW (47PS) @7250 rpm

Maximum Torque 52.3 Nm @5650 rpm Clutch Wet, multi-plate

Gearbox 6 Speed constant mesh Fuel Supply Electronic Fuel Injection

Air Cleaner Paper element

Engine Start Electric

Chassis & Suspension

Type Steel Tubular Spine Frame

Front suspension 43mm Upside Down Telescopic Fork, 120mm travel Rear suspension Twin Shocks, 101mm travel, preload adjustable

Electricals

Battery 12 volt, 12 Ah, VRLA Head Lamp FPL 1.55 W LED Tail Lamp 2.5 W, LED

Charging Port USB 2.0 Type A - 5V 2A Output

Dimensions

Wheelbase 1500 mm Ground Clearance 135 mm Length 2260 mm

Width 890 mm (without mirrors)

Height 1155 mm Seat Height 740 mm

Kerb Weight 241 kg (with 90% fuel & oil)

Fuel Capacity 15.7 litres

Brakes & Tyres

Tyres Fr. 100/90 - 19 M/C 57H (Tubeless Type)
Tyres Rr. 150/80 B16 M/C 71H (Tubeless Type)

Brakes Front Single 320mm disc, twin piston floating caliper Brakes Rear Single 300mm disc, twin piston floating caliper

ABS Dual Channel

COLOURS









CELESTIAL RED

(Tourer)

