

MAXXIS VICTRA SPORT 5


Performance when it's wanted. Safety when it's needed.

The Flagship **Maxxis Victra Sport 5**

(**VS5**) range is testament to Maxxis' significant commitment to research and development.

Designed for a vast range of car and SUV fitments, the VS5 offers superior levels of safety, comfort and overall performance, making it a compelling alternative replacement tyre fitment for all modern vehicles.

The VS5 has been a regular on the podium in Australian independent tyre tests.



A hybrid twist nylon/aramid cap ply **improves highway stability** while also **enhancing ride comfort**.



High performance polyester with very high denier in the body ply to **increase tensile strength and reduce weight**, produces **sharpened handling and steering response**.



Highly dispersible silica tread compound, processed through a new improved homogeneity mixing process, **delivers exceptional wet grip** while retaining **strong mileage performance**.



Chamfer edge tread blocks further **reduce wet braking distance** and **improve overall safety in the wet**.



MAXXIS®

VICTRA VS5

SIZE	TYPE	PATTERN	LOAD & SPEED	TREAD DEPTH (mm)	SECTION WIDTH (mm)	OVERALL DIA. (mm)	ROLLING CIRC (mm)	RIM WIDTH (in)
175/65R15	TL	HP5	84H	7.5	174	611	1830	5
185/55R15	TL	HP5	86V	7.7	192	587	1762	6
185/55R16	TL	HP5	83V	7.7	194	611	1851	6
185/60R15	TL	HP5	84H	7.7	190	606	1813	5.5J
185/60R16	TL	HP5	86H	7.7	190	629	1900	5.5
185/65R15	TL	HP5	88H	7.5	187	622	1866	5.5J
195/45R16	TL	HP5	84V	8	195	582	1778	6.5J
195/50R15	TL	HP5	86V	7.7	200	575	1742	6.0J
195/50R16	TL	HP5	88V	7.7	199	600	1818	6.0J
195/55R15	TL	HP5	85V	7.5	200	597	1809	6.0J
195/55R16	TL	HP5	91V	7.7	198	623	1888	6.0J
195/60R15	TL	HP5	88V	7.7	201	616	1866	6.0J
195/60R16	TL	HP5	89V	7.7	202	642	1945	6
195/65R15	TL	HP5	95V	7.5	204	635	1924	6.0J
205/40R17	TL	HP5	84W	7.7	215	598	1812	7.5J
205/45R16	TL	HP5	87W	7.7	209	589	1785	7.0J
205/45R17	TL	HP5	88W	7.7	206	619	1876	7
205/50R16	TL	HP5	91W	7.7	214	609	1845	6.5J
205/50R17	TL	HP5	93W	7.7	212	638	1933	6.5J
205/55R16	TL	HP5	94W	7.7	215	632	1915	6.5J
205/55R17	TL	HP5	95V	7.7	211	660	2000	6.5J
205/60R15	TL	HP5	91H	7.7	211	627	1900	6
205/60R16	TL	HP5	96V	7.7	208	653	1979	6.0J
205/65R15	TL	HP5	94V	7.5	209	646	1943	6
205/70R16	TL	HP5	97H	7.7	213	696	2102	6
215/40R17	TL	HP5	87W	8	218	604	1841	7J-8.5J
215/45R16	TL	HP5	90V	7.7	213	601	1821	7.0J
215/45R17	TL	HP5	91W	7.7	212	628	1903	7.0J
215/45R18	TL	HP5	93W	7.7	210	651	1942	7.0J
215/50R17	TL	HP5	91V	6.9	224	647	-	7.0J
215/50R17	TL	HP5	95W	7.7	224	646	1957	7.0J
215/50R18	TL	HP5	92V	7.7	225	673	2039	7.0J
215/55R16	TL	HP5	97W	7.7	223	644	1951	7.0J
215/55R17	TL	HP5	98W	7.7	223	671	2033	7.0J
215/55R18	TL	HP5	99V	7.7	224	695	2106	7.0J
215/60R16	TL	HP5	99W	7.7	219	667	2021	6.5J
215/60R17	TL	HP5	96H	7.7	222	690	2091	6.5J
215/65R16	TL	HP5	98V	7.7	219	686	2079	6.5J
215/65R17	TL	HP5	99V	7.7	223	710	2145	6.5
215/70R16	TL	HP5	100H	7.7	226	710	2151	6.5
225/40R18	TL	HP5	92W	7.7	232	640	1939	8.0J
225/45R17	TL	HP5	91W	7.7	225	636	1927	7.5J
225/45R18	TL	HP5	95W	7.7	225	661	2003	7.5
225/50R17	TL	HP5	98W	7.7	230	656	1988	7.0J
225/55R16	TL	HP5	99W	7.7	232	657	1991	7.0J
225/55R17	TL	HP5	101W	7.7	230	682	2066	7.0J
225/55R18	TL	HP5	98V	7.7	233	707	2142	7.0J
225/60R16	TL	HP5	98V	7.7	228	675	2045	6.5J
225/60R17	TL	HP5	99V	7.7	228	704	2133	6.5J
225/60R18	TL	HP5	100H	7.7	232	730	2191	6.5
225/65R17	TL	HP5	102H	7.7	233	727	2200	6.5
225/70R16	TL	HP5	103H	7.7	228	724	2198	6.5
235/40R18	TL	HP5	95W	7.7	242	648	1963	8.5J
235/45R17	TL	HP5	97W	7.7	237	644	1951	8.0J
235/45R18	TL	HP5	98W	7.7	236	672	2036	8.0J
235/50R17	TL	HP5	96V	7.7	242	669	2027	7.5
235/50R18	TL	HP5	97V	7.7	242	694	2103	7.5
235/55R17	TL	HP5	103W	7.7	245	691	2094	7.5
235/60R17	TL	HP5	102V	7.7	244	714	2150	7.0J
235/65R18	TL	HP5	106W	7.7	246	767	2322	7
245/40R18	TL	HP5	97W	7.7	249	655	1985	8.5
245/45R17	TL	HP5	99W	7.7	245	650	1970	8.0J
245/45R18	TL	HP5	100W	7.7	244	677	2051	8.0J
245/60R18	TL	HP5	105H	7.7	254	752	2258	7

E&OE. Maxxis Tyres Australia/Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this portal/publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Dimensions, measurements and technical specifications are based on manufacturer and tyre industry standards. Physical measurements of product may be within +/- 2 to 5% of what is stated here.