



High Quality Sealing Tapes

— Printed Tapes

Physical & technical Information

Backing Material:	Bi-Axial Oriented Polypropylene Film
Adhesive:	Pressure Sensitive Water Base Acrylic
Core Diameter:	76. 2mm +/- 0. 3mm
Printing Colors:	1color, 2 colors, multiple colors
Base color:	
Width Available:	75/72/60/50/48/45/38/36mm(serrated&standard) 25/24/19/18/ 15/12mm(standard)
Max.printing height:	6mm less than tape width(standard) 10mm less than tape width(serrated)
Max.repeating length:	500mm
Film Available:	23/ 25/ 28/32/35/38/40/60my(standard) 35/38/40/50/60my(serrated)
Thickness:	40my - 100my(standard) 55my-90my(serrated)



Printing Designs (Warning Tape)



Printing Designs (Customized Tape)

 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										 www.dhl.de										48mm									
																																																		48mm																																																											
TH AFRICA PUMA® - IF BROKEN PLEASE REPORT										PUMA® SOUTH AFRICA PUMA® SECURITY SEAL – IF BROKEN PLEASE REPORT										48mm																																																																																									
ND TY TAPE - BANDE DE SÉCURITÉ										LIDL - SICHERUNGSBAND LIDL - SECURITY TAPE LIDL - BANDE DE SÉCURITÉ										LIDL - SICHERUNGSBAND LIDL - SECURITY TAPE LIDL - BANDE DE SÉCURITÉ										48mm																																																																															
 CHINA POST (广东)										 CHINA POST (广东)										 CHINA POST (广东)										 CHINA POST (广东)										48mm																																																																					