




packserv
australia

Packaging Machinery
Made Easy

PFM-3-2C TWIN HEAD AUTO FILLER



PFM-3-2C TWIN HEAD AUTO FILLER

Our PFM-3-2C Auto Twin Head Up Filler is a semi-automatic liquid, paste and cream filling machine that is both user friendly and versatile. The heavy duty, all pneumatic design of the PFM-3-2C is compact, reliable and easy to clean.

The PFM-3-2C is designed with a completely automatic function for use in a full-scale production line. The machine is trolley mounted, with lockable castors allowing connection to a continuously running slat conveyor. The PFM-3-2C also comes complete with a “no bottle no fill” safety device and container gating system.

The PFM-3-2C also comes as standard with positive shut-off nozzles and a bottom up fill assembly. The valve system of the PFM-3-2C comfortably handles bottling hot or cold products from thin liquids to creams and thick pastes. An optional valve is also available for particularly hot fill applications i.e., those above 65°C.

ADDITIONAL INFORMATION

- Heavy duty pneumatic product cylinder drive system.
- All pneumatic flameproof operation suitable for use with flammable products.
- Features a frame mounted on castors/wheels for easy manoeuvrability.
- Easy volume adjustment while running a single cylinder.
- Adjustable piston fill and recharge stroke speed.
- Simple tool-free dismantling makes for easier cleaning.
- Quick changeover of products and parts.
- Suitable for liquids, creams and pastes.
- Filler is suitable for food and pharmaceutical use.
- Suitable for warm water hose down.
- Quick connect tri-clover product inlet/outlet fittings.
- Various methods to feed product to machine available.
- Features bottom up fill (BUF) to reduce foam/froth/bubbling of products.

PFM-3-2C TWIN HEAD AUTO FILLER

SPECIFICATIONS

- **Weight:** 75 kilograms.
- **Length:** 1400mm.
- **Width:** 1000mm.
- **Height:** 1700mm.
- **Power Supply:** Air compression
- **Construction Type:** 316 grade stainless steel wet parts.
- **Container Type:** Bottles, jars, tubs etc (any container type that will stand on a conveyor).
- **Mounting:** Trolley mounted with lockable castors (mounts onto inline conveyor system).
- **Industries:** All food, pharmaceutical and industrial applications.
- **Air Pressure:** 600kpa (80psi).
- **Units Per Minute:** 20-60UPM (guide only).
- **Noise:** Medium.
- **Flameproof:** Yes.
- **Timer Control:** Pneumatic.
- **Speed:** Adjustable for all functions.
- **Fill Range:** 2.5ml to 1250mls fill range, single shot.
- **Fill Temperature:** Cold and hot fill.
- **Fill Type:** Liquids, creams, lotions (suspended particles acceptable).
- **Not Suitable Products:** Dry powder and granules.
- **Benchtop:** Mounted to mobile welded frame featuring castors/wheels.
- **Machine Cleaning:** Easy to disassemble for full wash up. Volume: Fully adjustable.
- **Filling Accuracy:** +/- 0.5 to 1% variance.
- **Cylinder Sizes:** 25ml, 50ml, 125ml, 250ml, 500ml, 750ml or 1250ml.
- **Automatic Function:** Designed to be completely operator free.