XL800 PRODUCTIVITY APPLIANCE[™]



with Alphanumeric Graphics Display



THE CHALLENGE

You need a simple and effective way to improve manufacturing productivity. A way to gather actionable information that exposes problem areas, and a way to inspire and motivate the people that have the greatest impact on productivity – your plant floor employees. You need information fast – and at your fingertips. Not buried in a report that is days or weeks old. With resources and budgets already stretched thin, somehow you need to produce more with less. And you need an easy and affordable solution with no software to install, no contracts to sign, and installation measured in hours – not weeks or months.

THE SOLUTION

Introducing the XL800 Productivity Appliance[™]. A "bolt-on" performance management tool that is so easy to use that it can be self-deployed in about an hour. The XL800 automatically tracks production in real-time and instantly delivers meaningful, accurate, and actionable information anywhere in the world. We call it *Data Anywhere, Data Everywhere*[™]. The integrated large area visual display informs, alerts, and motivates your plant floor employees, while the built-in Ethernet LAN connection delivers instant production reports and analytics to supervisors and managers – wherever they are. All from one, low-cost, fully-integrated hardware appliance.

KEY BENEFITS

- A complete solution—plant floor scoreboard, production reporting system, historical analytics, and browser-based live data—all included.
- No software to install. Simply plug the XL800 into your LAN and it delivers instant plant floor performance data.
- No changes to your process. It's a "bolt-on" solution that easily connects to your existing process.
- No waiting. Instant production reports delivered in Excel[®], Word[®], and CSV formats.
- Live production data delivered directly to your desktop via a standard web-browser.
- Motivates plant floor employees to meet and exceed goals with real-time performance feedback.
- Eliminates time consuming and error-prone manual data entry.
- Tracks 100+ metrics including OEE, Target, Performance to Takt, Rate and Down Time.
- Exposes losses in real-time for immediate corrective action.
- Shows if process is on target (green), slightly deviating (amber), or requires immediate attention (red).
- Adapts to your process with intuitive browserbased configuration tools.
- Field proven with thousands of installations across all major industries.
- Self-deployed in about an hour.

FREE 90-Day Trial with expert technical support

WORK CLOW

Based Data uded!		Historical Analytics Included!							Production Reports Included!				
Lynner									#7	Shift Report - Assembly Cell #7			
Assembly Ce	k(0++) (10.1.16.237/	dia T				an case tag		Stop Tone Shaft KD	1 0141 104	_		_	t laformation
m Pedalite Tem Temp Peaks Sar Action S	Contraction of the second seco	1144	10.5% 00.5% 00.5% 00.5%	5.054 6.737 5.119 5.340 5.214	6.166 1.945 1.942 1.942 1.942	128	5.500 6.875 5.717 5.341 5.425	115/2007 10:00 First Shitt V16/2007 02:00 Secure Shitt V15/2007 10:30 First Shitt V17/2007 02:00 Secure Shitt V17/2007 02:30 First Shitt	3 5/15/3007 00:50 3 5/15/3007 10:50 4 5/16/2007 10:50 5 5/16/2007 10:50 5 5/16/2007 10:50	1.30000000 4.10000000 3.340000000	Bileal Cycles Takt Time: Average Cycle:	BD DE DE DE BD SE DE DE Frat Switt	A Starts 05/35/2007 R Bed 05/25/2007
a RPM PSG Good RPH 1	Total Count 5,000 Good Count 5,004 Reject Count 125	15115	12.27% 12.47% 52.27% 52.27%	8,710 8,151 8,910 4,019 4,315 8,536	1.798 1.846 1.845 1.827 1.888 1.526	549 560 437 404 107	1,120 6,344 1,347 5,020 5,020 5,020 6,020	V10/2007 62:00 Secure DVA V10/2007 16:30 First StvA V10/2007 62:00 Secure DVA V10/2007 16:30 First StvA V10/2007 16:30 Secure StvA	3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	2315 7415	OLE OLE Availabilitys Performance: One film	5,834 136 5,960 813	ef Creat of Creat of Creat of Creat
al 5,834 Peces to Goal ency 94.34%	OEE 32,71% Target Availability 26,19% Actual Performance 94,82% Efficiency	SALAS	17 57% 10 52% 12 77% 14 6%	6.540 5.530 5.590 5.890 5.890	1.301 1.301 1.307 1.307 1.308 1.308	65 258 467 467 465	6,519 6,220 6,211 7,000 6,515 6,515	100/2007 16:30 First Sett 10/2007 12:30 Second Sett 10/2007 16:30 First Sett 10/2007 16:30 First Sett 10/2007 16:30 First Sett 10/2007 16:30 First Sett	12 V392861 61 00 13 V392861 91 30 14 V292861 61 30 15 V292861 61 30 16 V292861 61 30 16 V292861 61 30 16 V292861 61 30 17 V292861 94 30	4.64	Tangaths and Starls Tangath	45.645	forthes Times
a Time 1:27:21 Percent Down 18.	Cycle Times Current Cycle Time (s) 1.22 Lest Cycle Time (s) 3.26 Down Tim	1105 B	91.80% 02.54% 12.91% 95.50% 92.61% 73.70%	1.195 1.161 5.600 7.625 7.300 6.907	1,808 1,719 1,885 1,995 1,217 1,981	175 347 101 508 298	1.550 1.454 5.546 1.728 7.710 6.850	V25/2007 16.30 First SHIT V26/2007 62.00 Securit SHIT V26/2007 62.00 Securit SHIT V25/2007 62.00 Securit SHIT V25/2007 16.30 First SHIT V25/2007 16.30 First SHIT	Ki M23/3887 67:00 T9 V23/3887 67:00 20 V23/2887 67:00 21 V29/2887 67:00 21 V29/2887 67:00 22 V25/2887 67:00 22 V25/2887 67:00	NAME.	Added Efficiency:	65.545 18.215 3.625 8.225 8.225 100.005	63613 12715 61712 61712 64000 64 600.00
	Average Cycle Time (s) 3.34 Standard Cycles 6,649 Ston Cycles 1,152 Small Stops 00	11.000 41.000 51.000 51.000	65.20% 81.20% 65.20% 65.20% 67.70%	5,252 6,247 5,368 7,251 5,215	1,004 1,004 1,017 1,010 1,010	410 740 60 001	5.437 6.963 6.112 7.314 5.416	129/2007 16.30 First Self. 127/2007 62:00 Second Self. 127/2007 162:00 Second Self. 129/2007 162:00 Second Self. 129/2007 163:00 First Self.	24 V282387 67:00 25 V282387 67:00 28 V282387 67:00 27 V282387 67:00 29 V282387 67:00	_		4,649 1,150 60	adard: 41254 11112 A Stop: 0244
	Standard Cycles Time 4:12:54 Slow Cycles Time 1:11:12 Singl State Time	11076 00.776	15.104	1,959 6,952 1,622	7.645 1.760 7.626	400	7.847 6.252 7.590 6.798	V29/2007 82:00 Second Stat V29/2007 93:30 Feed Stat V29/2007 82:00 Second Stat	29 V29/2007 14:30 30 V29/2007 07:00 81 V29/2007 14:30	Separate	Uner Strings	1136	- Realities

Productivity / Packaging / Performance NZ+64 3 579 2999 AUS+61 28 355 7035 www.wflow.co.nz

Shift Report – Assembly Cell #7									 B. Mich Page Interface - Dr. Scill. (pro: Agronto: 2) Address. http://dl.3.24.23 	- 945	narnet Explorer		-
Shift Start Shift Start Shift Start Shift Sh	66/16/2007 86/15/2007	00.00.00 16-00-00 First Swit	Maai Cy Tala Tin Arm an	towned front - Ann	1 Contraction				Carl September	-	1. 100. 100.001.0001.100	Assembl	
Council Gaussi Council Reject Council Total Council American ElPet		5,834 136 8,960 833	Otto Auto Park Qual	ADD +	& Amounting Cold at			A State	Total Court Good Court Reject Court	1,050 5,828 125	Average Rate (RPH) Tasai Atris 813 Good Atris 796 Report RPH 17	Current Rate () Tacui Affer Good Affei Regent R7H	L,103 L,103 0
Down	5 35 13 1 25 25 9 17 22	0.145 1.175	111	United for the second s	117/0007 82:00 Jocard Brit 917/2007 45:00 First Brit 918/2007 82:00 First Brit 918/2007 82:00 First Brit 919/2007 92:00 First Brit 919/2007 92:00 First Brit	1.341 6.620 7.100 6.644 7.341 6.644	STRATES.	「日本日本日本日本日本日本日本日本日本日本日本日本日本日本日本日本日本日本日本	OEE Assubility Aptomatics Overty	78.71% 76.19% 94.82% 97.83%	Target Counter Target 8,184 Actual 5,814 Efficiency 84,34% Time Variance (0:23/15	Goal Counter Coll Percent of Coal Percent of Coal	8.184 250 34.54%
Standby: Total	4 12 54	4540 4,540	an average	krejstaat? es aa ktajstaat? ef na Vederaat? es aa keavoes? es aa Vederaat? es aa Vederaat? es aa Vederaat? es aa Vederaat? es aa Vederaat? es aa	12202001 0210 Second Shitt 12202001 65 30 Pris Shitt 12202001 65 30 Pris Shitt 12202001 65 30 Pris Shitt 12202001 65 30 Pris Shitt 1220200 0210 Second Shitt 1220200 0210 Second Shitt 1220200 0210 Second Shitt	4.00 4.00 4.01 4.01 4.01 4.01 4.01 4.01	1012124	100 110 110 100 100 100	Cycle Times Current Cycle Time (s) Lest Cycle Time (s) Average Cycle Time (s) Standard Cycles Time Cycles	8.24	Production Times Run Time 1:20:10 Down Time 1:27:25 Selup Time 0:127:25 Standby Time 0:46:00 Production Make Ban	Prod. Time Per Percent Ruf. Percent Souri Percent Souri Percent Standar	18.21% 3.62% 8.17%

"SIX-IN-ONE" PRODUCTIVITY APPLIANCE™

The XL800 is an incredibly flexible performance management platform that combines six products into one simple package:

- Visual Display Informs, alerts, and motivates employees
- Production Monitor Tracks manufacturing performance
- **Data Warehouse** Manages real-time and historical data
- I/O Processor Provides flexible connectivity to your process
- Embedded Server Distributes data to managers everywhere
- Programming Platform Tailors operation to your process

VISUAL DISPLAY

The XL Visual Display provides instant performance feedback to the plant floor. Information that informs, alerts, and motivates your plant floor employees.

See Goals, Meet Goals

Goals are a powerful motivator, and the XL Visual Display establishes a shared set of goals for the plant floor. In fact, for most applications, the XL Visual Display is the fastest path to productivity gains. It channels people's natural competitive spirit and harnesses their desire to win by establishing SMART goals (Specific, Measurable, Attainable, Realistic, and Timely).

Focused Feedback

XL delivers the right information to the right people at the right time. It translates complex manufacturing data into easy-to-understand performance feedback. The result is a well informed, strategically-aligned workforce that is truly focused on improving productivity. Think of XL as a real-time performance dashboard for the plant floor.

Customizable - Not Custom

Every production situation is unique. That's why XL makes it especially easy to select the metrics that are most meaningful for your plant floor. With 100+ metrics available "out of the box", XL easily adapts to your needs. Plant floor events are immediately reflected on the XL Visual Display, providing a direct link between action (line goes down) and reaction (operator resolves problem).



Flip screens automatically based on what's happening on the plant floor.

PRODUCTION MONITOR

The XL Production Monitor connects to your manufacturing process with plug-and-play simplicity. Seven integrated modules provide metrics and KPIs that are critical to understanding and managing your production: Counts, Rates, Cycles, Production Times, Visual OEE™, Targets, and Goals.

NO SOFTWARE TO INSTALL!

XL provides instant browser-

based access to production

reports, historical analytics,

nd live plant floor data.

Easy Integration

Simply add one or two sensors and get a wealth of actionable information.

YOU PROVIDE	XL PROVIDES
One Sensor	Total Count, Current Rate, Average Rate, Current Cycle Time, Last Cycle Time, Average Cycle Time, Run Time, Last Run Event, Percent Run, Down Time, Last Down Event, Percent Down, OEE Availability
Second Sensor	Good/Reject Count, Percent Good/Reject, Good/Reject Rate, OEE Quality
ldeal Cycle Time	Standard Cycles, Standard Cycles Time, Slow Cycles, Slow Cycles Time, Small Stops, Small Stops Time, OEE Performance, OEE
Takt Time	Target Count, Pace Timer, Takt Timer, Count Variance, Time Variance, Efficiency
Goal	Pieces to Goal, Percent of Goal
Setup Switch	Setup Time, Last Setup Event, Percent Setup
Time Schedule	Standby Time, Last Standby Event, Percent Standby, Remaining Time

DATA WAREHOUSE

The XL Data Warehouse manages real-time and historical data with Registers and Streams.

Registers

Registers store real-time data such as the 100+ metrics generated by the XL Production Monitor. They also provide hundreds of "uncommitted" registers that can be loaded from PLCs, ERP systems, and other sources.

Streams

Streams store archived historical data, such as production records for the last 1,000 shifts and 1,000 jobs.

I/O PROCESSOR

The XL I/O Processor provides flexible connectivity to your production process.

Digital Inputs

Six (6) high-speed digital inputs, plus sixteen (16) expansion inputs option.

Digital Outputs

One (1) standard relay output, plus six (6) expansion relay outputs option.

Relay outputs are for annunciation only, and are not designed or intended for control applications.

Communication Ports

Three (3) communication ports are standard: 10/100 Ethernet, RS-232 and RS-232/RS-485 (selectable).

©2008-2011 Vorne Industries, Inc. All rights reserved. Prices and specifications subject to change without notice. Please reference the Product Warranty Statement and Sales Terms and Conditions. Vorne Industries, Inc. makes no warranties express or implied except as expressly stipulated in our Product Warranty Statement. Free 90-day trial offer is for qualified manufacturing applications only. Vorne, Visual OEE, Productivity Appliance, Data Anywhere, Data Everywhere. and We Improve Manufacturing Productivity are trademarks of Vorne Industries. All other trademarks are the property of their respective owners. REWISION 201108

EMBEDDED SERVER

The XL Embedded Server provides instant access to production data for supervisors and managers—from anywhere in the world—with no software to install.

Data Anywhere, Data Everywhere

Supervisors and managers can view live production data and download shift and job reports in Excel®, Word®, and CSV formats—all via a standard web-browser.

Documentation Center

No lost manuals, no out-of-date information, and no digging for documentation. The XL Documentation Center delivers instant access to complete XL documentation direct from XL via web browser.

PROGRAMMING PLATFORM

The XL Programming Platform makes it easy to tailor XL operation to your specific requirements. Create application specific programs by simply stringing together predefined commands to achieve your desired operation.

Time Schedules and More

Programs can be automatically triggered by time schedules, inputs, presets, production state changes, and more.

Unlimited Applications

- Drive a stack light based on line speed or downtime
- Automatically display remaining time for breaks
- Create "custom" metrics and KPIs
- Create a maintenance call button with a response timer

SPECIFICATIONS

Visual Display

- Full matrix display field 32 x 80 pixels
- Tricolor (Red/Green/Amber) LED, 12 shades plus effects

Digital I/O

- Inputs 5 to 24 VDC Sink/Source
- Outputs 1A, 120 VAC, SPDT Relay

Electrical

- Voltage: 100 to 240 VAC
- Power: 100 Watts

Mechanical

■ 35 cm (H) X 67 cm (W) X 9 cm (D); 9 kg (Weight)



Access your data anywhere, including right on your iPhone™!

FREE 90-DAY TRIAL

XL is an easy and complete solution that will save you significant time and money. We'll prove it! Try an XL unit in your plant for 90 days. After 90 days, simply return it or pay for it.

WORK:

Clow

NZ +64 3 579 2999 AUS +61 28 355 7035