

OneWrap Pallet Wrapper

NEW PANEL IS DIVIDED INTO 4 MAIN AREAS:



Section for mode of operation selection

Parameter setting for cycle characteristics

Display area with selection arrows

Section for start/stop/homing and power switch, ready and emergency stop



A semi-automatic machine for wrapping palletized loads with stretch film. It can be equipped with mechanical/electromagnetic brake or powered pre-stretch carriages.

- Modern design with enclosed motors
- Turntable Robustness: Best in class load capacity up to 2.4 tons!
- M Carriage: higher grip and better performing tension roller
- New LP Carriage with 240% power prestretch as standard
- Ease of maintenance (accessibility & wiring)
- Parts simplification and rationalisation
- Reduced footprint and transport size
- Warranty 24 months
- IP65 control panel
- Film Break detection: Logic board will interrupt the cycle automatically in case of film break (function available with LP carriage only)
- A sleek and modern design of the column with easily understandable icons

Key Features

- Belt driven carriage
- Pallet height photocell
- Reclining column hinged to the base facilitates installation and possible repositioning
- Turntable locking feature to avoid movement during loading/unloading operations
- Power 240V single phase
- Low profile 75mm turn table
- 1650mm diameter turn table
- Max pallet height 2200mm
- Anti-crush switch on carriage

New Features

- Cycle can be stopped at any point and then continued, very useful for corner protection application
- A two digit large display is used to visualise the parameters to be adjusted such as speed, number of wraps etc. As well as error code display. Improved ease of use

Victoria

37 Latitude Boulevard
Thomastown VIC 3074
Australia
T (03) 9474 3800
F (03) 9464 1504

New South Wales

2/17-19 Daniel Street
Wetherill Park NSW 2164
Australia
T (02) 9756 5433
F (02) 9756 0511

Queensland

2/16 Yarraman Place
Virginia QLD 4014
Australia
T (07) 3865 6089
F (07) 3865 3799

W www.cpspackaging.com
E info@cpspackaging.com

