



ITL Series

Integrated Top Load Case Packers



BW Integrated Systems' ITL 15 & ITL 25 Integrated Top Load Case Packers are fully automatic robotic or gantry case packers capable of top loading your product into RSC or HSC cases. A variety of pick heads are available, including vacuum, mechanical, and combination vacuum/mechanical styles to accommodate almost any product.

Both models are ideal for various case styles including tear-out display cases, HSC (available case lid attachment), and are capable of packaging cartons, tubes, pouches (flat and stand up), jars, F-style jugs, and round bottles.

ITL 15 / ITL 25 Integrated Top Load Case Packers

The ITL 15 and ITL 25 solutions feature a low, ergonomic KD case magazine, small overall footprint, and are ideal for nearly all production environments. Construction is available in dry, wash-down, or caustic wash-down options. The modular design allows for multiple infeed configurations as well as the ability to feed bliss cases or trays into the system. Case opening is securely handled with opposed vacuum cups and positive case transfer is accomplished with servo-driven side belts. Case sealing can be either standard tape or optional hot-melt closure. Tool-less changeover is completed simply and quickly with hand crank handles.

The **ITL 25** system includes high-speed case set-up for increased throughput capacity.

Contact our experienced sales teams today for a comprehensive review of your application(s) and to see how our ITL Series Integrated Top Load Case Packers can benefit your company.

FEATURES

- Fully automatic case packer with modular design
- Accommodates a wide variety of products
- Opposed vacuum case opening increases reliability
- Tool-less changeover completed quickly with hand-crank handles
- Tape sealing
- Low profile, ergonomic KD case magazine
- Vacuum pick-head
- Compact footprint
- PackML compliant
- Soft metric design

AVAILABLE OPTIONS

- Robotic loading
- Wash-down construction
- Hot-melt sealing
- Mechanical and custom pick heads
- Flexible infeed layout/ configurations
- Additional magazine length

Specifications

Case Dimensions Setup

Length: 8" - 20" (20.32 cm - 57.15 cm)

Width: 5" - 14" (12.70 cm - 35.56 cm)

Depth: 5" - 15" (12.70 cm - 38.10 cm)



Various products run on the ITL 15



ITL 25 Integrated Top Load Case Packer