

CHOIC/

Features:



Tension Speed

Powered By

Bosch



Cleaning



Interface

STB 75

Strap Alignment Guide Protective Design

Lightweight & Perfect Balance

Strapex Model	STB 73	STB 75
Operation Mode	Auto/Semi/Manual	Auto/Semi/Manual
Tension Force Range	400 - 2500 N	400 - 4500 N
Variable Tension Speed	0 - 220 mm/s	0 - 120 mm/s
Weight (Inc. Battery)	3.8 kg	4.3 kg
Dimensions	370 x 141 x 135 mm	370 x 143 x 135 mm
Working Temperature	-10° to +40°	-10° to +40°
Cycles / Charge	up to 800	up to 800
Battery	BOSCH Li-Ion 18V, 2.0Ah	BOSCH Li-Ion 18V, 4.0Ah
Charging Time Battery	15-30 mins	25-35 mins
Strap Type	PET + PP	PET + PP
Strap Width	13 - 16 mm	16 - 19 mm
Strap Thickness	0.5 - 1.0 mm	0.8 - 1.3 mm
Motor technology	Single motor technology, brushless	Single motor technology, brushless

Favourite

Presets



DESCRIPTION

4641	STB 73 Strapping Tool 18V	
4642	STB 75 Strapping Tool 18V	
366.073.001	Protective Cover	
366.740.001	Wear Protection Plate	
4668	STB 73 Replacement Battery 18V - 2.0Ah	
4667	STB 75 Replacement Battery 18V - 4.0Ah	





Accessories:



USER INTERFACE COVER For additional protection in harshest environment





PROTECTION PLATE For usage on abrasive surfaces





SUSPENSION BOW For stationary application

1300 525 325

TIGERPAK.COM.AU

LIGHTWEIGHT & PERFECT BALANCE

Ergonomic design to reduce operator fatigue and discomfort. Perfect weight distribution for one-handed use.

VARIABLE TENSION SPEED

Pressure-sensitive tension button grants you unmatched control of tension force while strapping.

Allows incremental tension speed adjustment to suit every job from small fragile packages to the heaviest applications.

المربع SMART-TOUCH INTERFACE

New-generation Strapex range is the world's first strapping tool featuring full touchpad controls and smart colour indication. Always on display is realtime status of device parameters to offer complete, uncompressed navigation and control for every job.



FAVOURITE PRESETS

Smart-save feature allows you to store your favourite strap function and settings, allows the user to quickly switch between your most common strapping applications.

EASY CLEANING

Integrated blow channel allows effortless cleaning of the tool without disassembly.

PROTECTIVE DESIGN

Robust housing survives up to 2-metre* drops, providing durability and extra security.

STRAP ALIGNMENT GUIDE

Safety indicator detects strap position to indicate correct placement and positioning. This guarantees every application is errorfree and precise, preventing damage to the strap or product surface.

POWERED BY DOSCH

BOS

Best-in-class battery life with quick charge, Li-lon technology to eliminate memory effect and CoolPack active temperature management ensuring more applications per battery cycle.





1300 525 325 TIGERPAK.COM.AU