





we dare to try anything



Reliable & efficient wrapping machines

+ HIGH CAPACITY: up to 120 pallets/hour

- + Maximum quality, high performance and minimum maintenance
- + It is the most versatile: it can evolve to a Saturn S8 model to get higher capacities
- + The load remains static: the film reels rotate around the load
- + Guaranteed savings of stretch film: 300% film pre-stretching
- + 1 m of film becomes 4 m
- + Finishing without tails of film thanks to our efficient cut and welding device
- + Electronic and self-adjusting tension control depending on the profile of the load
- + Possibility of applying efficient dustproof and rainproff wrappings
- + Possibility of wrapping at ground level
- + Capable of applying bands (strips) at any height of the load

Standard equipment





Optionals





Saturn S6



Saturn S6

Automatic rotating ring stretch wrapping machine



		D17	D20	D23	D26	D29
PRODUCTION	Maximum capacity (p/h)	120	110	90	85	75
MACHINERY DIMENSIONS	A (mm)	7	000		10000	_
	B (mm)		000		3000	
	C(mm)	3	000		4000	
	D (mm)	2	000		3000	
	E (mm)	3600	3800	4260	4	560
	F (mm)			4200 *		
	G (mm)			2600 *		
	H (mm)	2300	2500	3150	34	450
LOAD DIMENSIONS	Maximum width (mm)	1100	1300	1500	18	300
	Maximum diagonal (mm)	1750	2050	2300	2600	2800
	Maximum height (mm)	2100 (onveyors height 500 mm) *				
POWER SUPPLY	Voltage	400 V 3P + N + PE 50 Hz				
	Compressed air pressure (bar)	6				
STRETCH FILM	Maximum height (mm)		51	00		
	Maximum diameter (mm)		2	50		
	Inner core diameter (mm)		7	6		
	Film thickness (μ)	up to 35				
TOP FILM	Maximum height (mm)	1600	1800	2000	24	400
	Maximum diameter (mm)		31	00		
	Inner core diameter (mm)			6		
	Film thickness (μ)		4	0		

 \star Possibility to adapt the frame of the machine for loads higher than 2100 mm









😢 🖸 🗑 🕒 www.movitec-ws.com

AUSTRALIA/NEW ZEALAND Packaging Solutions & Equipment Pty Ltd 1300 773 1000