# boxford

### **CNC Routers**

The Boxford range of 3-axis CNC high performance routers are ideally suited to fulfil all levels of education and training requiremens, as well as a host of design and commercial applications.

Manufactured in the UK, the rigid machine construction, incorporating high quality precision components, facilitates the use of high material removal strategies, giving a component throughput that lower quality machines of lighter construction cannot match.



See our full range of manufacturing systems for education, design and industry on our website: www.boxford.co.uk or call us on +44 (0)1422 324810

# boxford



### A3HSRmi<sup>2</sup>

Bench top CNC routers suitable for machining hardwood, softwood, manufactured boards, plastics, other synthetic materials, aluminium alloys and brass.



### A3HSRmi<sup>2</sup> EX

Extended capacity versions of the A3HSRi<sup>2</sup> and A3HSRmi<sup>2</sup> machines, offering 350mm extra machining area to accomodate a larger variety of work.



#### A1HSRi<sup>2</sup>

Large format floor-standing router suitable for machining hardwood, softwoods. manufactured boards, plastics and other synthetic materials.

#### Standard features:

- USB interface
- Tooling starter pack
- Single seat of Boxford 'CAD/CAM Design Tools' software (incorporating Techsoft 'Mill Design' & import wizards for creating 2,3 and 4 axes machining routines from 2D and 3D CAD files, JPEG and BMP image files and Gerber PCB files)

Optional accessories:

- Removeable vacuum bed
- Manual rotary indexer
- Auto rotary indexer
- PCB floating head kit
- Lathe attachment
- Portable cabinet base
- Extraction manifold kit
- High performance extractor
- Standard extractor

Specifications	A3HSRmi <sup>2</sup>	A3HSRmi <sup>2</sup> Ex	A1HSRi <sup>2</sup>
Axis travel X (Longditudonal) Y (Cross) Z (Verticle) Table area	575mm 325mm 130mm 750x400mm	925mm 325mm 130mm 1100x400mm	1235mm 625mm 130mm 1295x720mm
Spindle motor Spindle speed	1000 watts 8000 - 23,000rpm	1000 watts 8000 - 23,000rpm	1000 watts 8000 - 23,000rpm
Electrics	/ I	220/240 V 1phase	0000 - 20,0001pm
Programmable feed	5000mm/min	5000mm/min	6000mm/min
Rapid feed rate at 100%	5000mm/min	5000mm/min	6000mm/min
3D profiling up to	8500mm/min	8500mm/min	10,000mm/min
Aluminium alloys/brass	YES	YES	NO
Machine weight	150kg	190kg	530kg
Max dimensions (w x d x h mm)	1050x750x740	1400x750x740	1890x1200x1540

See our full range of manufacturing systems for education, design and industry on our website: www.boxford.co.uk or call us on +44 (0)1422 324810