

POLYFORM REPAIR SYSTEM



Polyform is a flexible external repair system for leaking and damaged pipelines. Polyform has a **50 YEAR LIFE** standard.



GAS



ELECTRICITY



OIL



WATER

NO GRIT BLASTING REQUIRED

The Polyform™ System is a two-part sealant that once mixed together will form a non-slumping robust consistency that can be applied to repair any shape and size main or fitting. It is approved to **GIS LC8 and DIN 30658**.

The system is currently available to seal both low pressure and medium pressure with the addition of venting hoses.

Independent studies show that Polyform™ delivers labour savings as a result of the universal fitting; ease of application, less time required on site.

Ideal for situations where the pressure cannot be reduced, or the pipe flow cannot be stopped.

FEATURES

- **No Grit Blasting** for L/P Repairs
- **50 year life** standard
- Low Odour
- Labour Reduction
- Permits pipe movement
- Excellent flexibility
- Waterproof once cured
- Inert Waste

APPLICATIONS

- Gas
- Waste Water
- Oil
- Chemical

PRESSURE

- Low Pressure 75 mbar
- Medium Pressure 2 bar

PIPE MATERIALS

- Steel
- Cast Iron
- Ductile Iron
- Plastic
- P.E. (Polyethylene)

ADDITIONAL EQUIPMENT

- Low Pressure Kit
Specialist film for encasing repairs comes with application spatula, mixing tool and protective gloves.
- Precoat Kit
Moisture curing dispersant, which draws the moisture off the pipe, enabling sealant adhesion. Comes with sponge applicator, abrasive roll and protective gloves.



MW Polymer Products Limited The Sidings, Duffield Road Industrial Estate, Little Eaton, Derby, DE21 5EG

+44 1332 835001 | admin@mwpolymers.co.uk | mwpolymers.co.uk