

# ECOSEAL REPAIR SYSTEM



Non toxic external injection system for the repair of leaking pipe joints.  
Eco seal repair system has a **50YEAR LIFE** standard.



GAS



ELECTRICITY



OIL



WATER

Eco seal is a two-part sealant that provides a quick and effective non-hazardous external mains repair system, that is approved to GIS LC25.

The sealant is suitable for applications for the repair of all joint types. Joints can be repaired by injection through the socket or directly through the lead joint face.

The sealant comes in three viscosities Red (Thick) for mechanical joints or where the yarn has totally decayed, Yellow (Thin) for lead yarn joints or Green (Ultra-Thin) for tightly packed joints.

Eco seal is highly flexible and ideal for use in areas where there is excessive ground movement including areas with levels of high traffic and earthquake prone zones.

**APPROVED TO GIS LC25 SPECIFICATION AND DIN STANDARDS**



## FEATURES

- Non-Toxic
- Environmentally Friendly
- 50-year life standard
- No Odour
- Inert Waste
- Labour Reduction
- Permits pipe movement
- Excellent flexibility
- Waterproof once cured

## APPLICATIONS

- Lead Yarn Spigot
- Mechanicals
- Socket joints
- Valves



## PRESSURE

- Up to and including 2Bar
- For higher pressure please contact MW Polymers directly

## PIPE MATERIALS

- Steel
- Cast Iron
- Ductile Iron
- Plastic P.E (Polyethylene)
- For damages to P.E & Plastic pipe please refer to the P.E data sheets

## ADDITIONAL EQUIPMENT

- Injection Line & Dispenser Required for Injection



MW Polymer Products Limited The Sidings, Duffield Road Industrial Estate, Little Eaton, Derby, DE21 5EG

+44 1332 835001 | admin@mwpolymers.co.uk | mwpolymers.co.uk