



# Maxprobe™ 120

## Datasheet

The Maxprobe™ 120 is the largest reel in the Scanprobe Techniques push-rod camera system family, with a longer and thicker rod for the bigger jobs. With the same user-enhancements and stability features as the rest of the Maxprobe™ range, including a sunlight readable screen and pneumatic tyres, this is the ultimate big brother.



<b>Weight</b>	
- Reel	49kg
- Box	5.5kg
<b>Rod Length</b>	120m
<b>Rod Diameter</b>	14mm
<b>Meterage Counter</b>	Yes
<b>Voltage</b>	12v DC / 230v AC / 115v AC
<b>Current</b>	Ex Power Supply - 1.7A Max
<b>Operating Temp.</b>	-10°C - +50°C
<b>Charging Temp.</b>	0°C - 40°C
<b>Battery</b>	Li-ion (9hrs running time)
<b>Dimensions</b>	
- Reel	1280mm x 840mm x 530mm
- Box	360mm x 290mm x 160mm
<b>LCD Display Size</b>	10.4"
<b>Resolution</b>	800 x 600 RGB (SVGA)
<b>IP Rating</b>	
- Reel	IP68
- Box	IP54
<b>Sonde</b>	
- Frequency	512Hz / 33kHz Optional
- Location	Camera Head
<b>Storage</b>	
	- 32Gb—1Tb HDD
	- 2x USB 2.1 ports
<b>Software</b>	
	- WinCan Embedded
	- mina reporting software
<b>Output</b>	800 x 600 SVGA. DE15 socket WiFi
<b>Video</b>	MPEG4
<b>Image Format</b>	JPEG



**WinCan**



**mina**®

Scanprobe Techniques Ltd.  
Unit 11, Kenley Trade Park, Old Barn Lane  
Kenley, Surrey, CR8 5AU

Tel. (0)203 253 2001  
Email. sales@scanprobe.com  
Web. www.scanprobe.com