



PCLX 32 + & 40 +

The PCLX 32 & 40**E+** are high-performance battery-powered lightweight plate compactors designed for professional and rental use. Featuring an emission free, **82v** Li-ion battery-powered motor for all your compaction requirements, indoor usage and poorly ventilated areas.

Produces low HAV values and matches the high performance compaction of its petrol powered equivalent, but without the environmental impact...

...Building a Sustainable Future!

FEATURES & BENEFITS

- Engineered to be robust and durable for rental and heavy contractor usage.
- Lightweight yet durable for easy transport. Fits in a standard car boot when the handle is folded.
- Low Hand-Arm Vibration design for longer safe usage times.
- High performance 13kN vibration unit gives excellent compaction force and travel speeds.
- Environmentally friendly, emission free for use indoors & in poorly ventilated areas such as basements and tunnels.
- Can be operated in environmentally sensitive areas, such as green spaces, nature reserves, national parks, rural railway cuttings and emission controlled urban areas, without any exhaust emissions.
- No routine power unit maintenance eliminates servicing or costly downtime due to repairs.
- Avoid problems with modern fuels. No blocked carburettors.
- Cordless design gives added operational flexibility.
- Quick release / connect 82v battery with digital power level display.
- 82v batteries are interchangeable with the other products in the Altrad Belle E+ 82v range, for added convenience and flexibility.
- Baseplate designed for optimised speed and manoeuvrability.
- Fitted with manual handling points.
- Easy to operate and control, the baseplate does not dig in when dragged backwards or turned.
- Optional paving pad for block paving applications available.
- Customer colour options available.

TECHNICAL SPECIFICATIONS

Model Motor Power Motor Type	(Hp / kW)	PCLX 32E+ 2.0 / 1.5 Brushless	PCLX 40E- 2.0 / 1.5 Brushless
Width	(mm)	320	400
Operating Height	(mm)	910	910
Operating Length	(mm)	1060	1060
Storage Height	(mm)	500	500
Storage Length	(mm)	780	780
*Weight	(Kg)	57	62
Static Pressure	(kg/m²)	397	337
Centrifugal Force	(kN)	13	13
Frequency	(Hz)	101	101
Max. Gradient	()	20	20
Max. Travel Speed	(m/min)	20	20
Vibration level	(m/sec ²)	<2.5	<2.5
Sound Power Level *weight without battery i	(dB L _{WA}) included.	105	105

Options

OPM/13/DIO82v 5Ah BatteryOPM/14/DIO82v 8Ah BatteryOPM/16/DIO82v Battery Charger (UK)OPM/19/DIOStorage Box (Box only)
(Able to store 2 x Batteries & 1 x Charger)



EMISSION FREE, 82V LI-ION BATTERY POWERED MOTOR



82V BATTERY, INTERCHANGEABLE WITH OTHER PRODUCTS IN THE ALTRAD BELLE E+ 82V RANGE



FOLDABLE HANDLE DESIGN FOR EASE OF STORAGE

Battery Battery Type Weight Width Height Length Voltage: Nominal Voltage Energy Rating Energy Capacity	(kg) (mm) (mm) (v) (v) (v) (Wh) (Ah)	5Ah Li-Ion 2.8 90 214 120 82 72 360 5.0	8Ah Li-Ion 3.9 90 240 120 82 72 580 8.0
0	()		





ALTRAD BELLE Sheen, Nr. Buxton, Derbyshire, SK17 OEU, GB Tel. +44 (0)1298 84606 - Fax +44 (0)1298 84722 Email: sales@altrad-belle.com www.Altrad-Belle.com www.Altrad-Belle.247.com