



BELLE
LIGHT
CONSTRUCTION
EQUIPMENT



Altrad-Belle.com

MBX 12/180

MINI BOWSER PRESSURE WASHER

The 125-litre MBX 12/180 Mini Bowser Pressure Washer is designed to satisfy the demands of individuals who need maximum mobility without compromising performance.

It guarantees a sufficient water supply for cleaning tasks whilst on the go and has the power to remove even the toughest dirt and grime from a range of surfaces.



BUILDING A SUSTAINABLE FUTURE

FEATURES & BENEFITS

- Robust, compact full engine & pump protection frame complete with hose storage facility as standard.
- 125 litre durable polyethylene water tank with filler strainer as standard.
- Professional Honda petrol engine with recoil start.
- Detergent / chemical feed-line complete with strainer filter.
- Single point lift to minimize manual handling risk.
- Accessible service points.
- Inlet-line strainer for added pump protection.
- Low engine oil cut-off.
- High quality, heavy-duty triple piston pump.
- Professional two-wire, 10m braided hose, complete with quick-screw adapters and swivel couplings.
- Thermal pump protection.
- Lance holder integrated into protection frame.
- Lance comes complete with safety trigger lock.
- 4-ply deep-tread tyre as standard.
- Specifically designed for hire and rental markets.
- Customer colour options available.
- Optional 10m Hose Reel available.
- Puncture-proof foam filled tyre option available.

TECHNICAL SPECIFICATIONS

Model		MBX 12/180 Standard	MBX 12/180 cw Hose Reel
Part No.		MBX12180S	MBX12180RS
Length	(mm)	1378	1378
Width	(mm)	760	760
Height	(mm)	885	885
Unladen Weight	(kg)	*91	**100
Max. Laden Weight	(kg)	#223.5	##227
Water Flow	(lpm)	12	12
Max. Water Pressure	(bar-psi)	180-2600	180-2600
Engine		Honda GX200	Honda GX200
Engine Power	(Hp / kW)	5.8 / 4.3	5.8 / 4.3
Engine RPM		3400	3400
Water Tank Capacity	(Ltrs)	125	125
Fuel Tank Capacity	(Ltrs)	3.1	3.1
Hose Length	(M)	10	10
Tyre Size	(mm)	400-8	400-8
Tyre Pressure	(psi - bar)	30 - 2.1	30 - 2.1
Gearbox Driven Pump		Yes	Yes

* without lance and hose. ** without lance.
with lance and hose. ## with lance.

Options

OPPW/08/DIO 80108	10m Hose Reel Kit Puncture Proof Tyre
----------------------	--



HOSE STORAGE INTEGRATED INTO PROTECTION FRAME



TANK FILLER STRAINER AS STANDARD



HOSE REEL OPTION



PUNCTURE PROOF, FOAM-FILLED TYRE OPTION