

ANCILLARY PRODUCTS

Anker Stuy Coatings provides a range of ancillary products to complement our coatings and offer a complete system. These products are an important addition to ensure the success of the protective coatings.

25-0353-X-1 Hydrolux End Grain Sealer White/Clear



Hydrolux End Grain Sealers is a water-borne primer sealer for end grains. Suitable for sealing cut-edges on window frames and other exterior joinery pieces.

99-000 Frencken Window Frame Adhesive



A high-quality single-component elastic adhesive suitable for bonding the joints in window and door frames and provides exceptional waterproofing qualities to the joint.

19-0277 Frencken Cleaning Wipes



Cleaning wipes dissolve fresh and uncured adhesive residue on hands, tools, workbenches, and other surfaces.

19-0200-500ml Frencken Cleaning Spray



Used in conjunction with the Frencken 0819 SLS window frame adhesive. It is especially designed for removing excess adhesive that squeezes out of the joinery after the joint is compressed.

19-0257-900ml Frencken Woodfiller



A ready-to-use and high-quality filler and levelling compound for filling longitudinal cracks as well as repairing minor damage and levelling out small irregularities and pores in the wood substrates.

25-0353-BL-250ml Hydrolux V-Joint Sealer



An easy to use V-joint sealer designed to offer additional protection in sealing v-joints in window frame profiles.

One-stop-shop Mirka® products & more



We offer various ancillaries, sundries and other practical items for the interior & exterior joinery industry.
✔ Mirka abrasives ✔ Frencken adhesives
See all products on www.ankerstuy.co.uk

EXTERIOR JOINERY COATINGS

Anker Stuy exterior products can be used on all external wooden elements, such as window frames, doors, garden furniture, tongue-and-groove boards, and other wooden façade features.

Our goal is to protect the wood for as long as possible against the elements. The British weather will quickly ruin beautiful wood if left unprotected. Our products are specifically formulated and tested with this in mind, ensuring high gloss retention and minimal colour degradation. This protects the wood for longer and requires less maintenance for the property owner.



KOMO ACCREDITATION

All Anker Stuy products are rigorously tested to KOMO certification. The KOMO certification is an international quality standard that provides guarantees for both the supply and demand sides of the building industry. The testing requirements are far more demanding than with European standard EN927 and result in a superior product. To find out more about KOMO visit www.ankerstuy.com



WE MAKE PAINT SPECIAL

SUSTAINABLE & INNOVATIVE SINCE 1898

Address

Unit 26 Alpha Business Park
Mallard Road
Peterborough
PE3 8AF

Phone

01733 215 444

E-mail

info@ankerstuy.co.uk

Website

www.ankerstuy.com



EXTERIOR WINDOWS AND DOORS

WE MAKE PAINT SPECIAL

SUSTAINABLE & INNOVATIVE SINCE 1898



PRIMERS

17-0537 Hydrolux Iso Primer



The 17-0537 Hydrolux Iso Primer is a premium, waterborne, tannin blocking and filling industrial primer for exterior windows and doors based on Tri-Cryl® technology.



- ✓ Forced dried in as little as 30 minutes.
- ✓ Amazing coverage at 175/200 microns
- ✓ Unrivalled tannin blocking

17-0535 Hydrolux Baseprimer



The 17-0535 Hydrolux Baseprimer is a water-borne opaque industrial primer that keeps the natural look of wood and can be tinted to any colour. Suitable for parts made from softwood and hardwood and for industrial application on front joinery.




- ✓ Forced dried in as little as 30 minutes.
- ✓ Incredibly low early water uptake
- ✓ Tintable to any colour
- ✓ Developed for use in a two-coat system

17-0540 Hydrolux Filling Primer



The 17-0540 Hydrolux Filling Primer is a high build industrial primer specially formulated for quick-drying to fill the grain and to achieve a uniform, smooth surface that also hides laminations and finger joint connections.



- ✓ Quick-drying primer
- ✓ Excellent coverage and filling properties
- ✓ Very good adhesion to all commonly used wood species

Primers also available in flowcoat

SYSTEM OVERVIEW

1. PRIMER	2. MIDCOAT	3. TOPCOAT
Hydrolux Primer	Hydrolux Primer	Hydrolux Topcoat
Hydrolux Primer	Hydrolux Topcoat	Hydrolux Topcoat
Hydrolux Primer	Hydrolux Topcoat	-
-	Hydrolux Topcoat	Hydrolux Topcoat
-	Hydrolux Topcoat	Hydrolux Topcoat
Impregnating Woodstain	Woodcoat TP	Woodcoat TP


- Forced dried in 30 mins
- Non-sagging up to 400µm
- Up to 15 years maintenance-free
- Low water uptake
- KOMO certified
- Designed for North Sea climates

IMPREGNATION

17-0699 Hydrolux Impregnation



The 17-0699 Hydrolux Impregnation is a water-borne translucent impregnation primer for preventive protection of timber against fungi according to EN 152 and EN 15457. This primer is based on acrylic resins with 0,95 % of IBPC. Approved biocidal product according to regulation (EU) 528/2012. The 17-0699 Hydrolux Impregnation is designed for:



- ✓ Saturation spraying
- ✓ Dipping
- ✓ Flow- or vacuum coating

Available in clear, opal white, and selected translucent colours and can be over-coated with Hydrolux and Ankolux Aqua exterior systems.

OPAQUE TOPCOATS

17-0648 Hydrolux Topcoat SM



The 17-0648 Hydrolux Topcoat SM is a waterborne, thixotropic topcoat based on Tri-Cryl® technology. The Hydrolux topcoat combines amazing coverage with superb flow. The Topcoat can be force dried, which means that you can proceed with further treatments after 3 hours.



- ✓ Touch dry within an hour
- ✓ Non-sagging up to 400 µm
- ✓ Incredible wet weather protection

Also available in 17-0649 Semi-Gloss (45% GU) & 17-0650 Gloss 70% GU


Can also be used in a KOMO certified 2-coat system

TRANSLUCENT SYSTEM

16-0201 Ankolux Aqua Impregnating Woodstain



The 16-0201 Ankolux Aqua Impregnating Woodstain is a non-film forming woodstain. It can be used as a standalone product in 3 coats for a non-film forming finish for non-dimensionally stable joinery such as cladding or decking, or can be used as an impregnating woodstain in conjunction with 16-0221 Ankolux Aqua Woodcoat TP.



- ✓ Very good adhesion on bare wood
- ✓ Great penetration into wood
- ✓ Excellent resistance to UV radiation

16-0221 Ankolux Aqua Woodcoat TP



The 16-0221 Ankolux Aqua Woodcoat TP is a waterborne, translucent, semi-matt midcoat and topcoat. Highly translucent semi-film forming finish that accentuates the natural grain of the timber. Quick drying, very durable, and a semi gloss finish of 45% GU.



- ✓ Incredible wet weather protection
- ✓ Exceptional hard-wearing finish
- ✓ Translucent appearance accentuating the woodgrain

Available in a wide range of translucent colours

EXTERIOR WINDOWS AND DOORS

