

ANTI SLIP

CERTIFIED SURFACES TO WALK ON



Manufactured using chemical etching, anti-slip floor glass provides solutions to incorporate the design flexibilities of glass with the functionality of traditional flooring materials. Implemented via special combinations of raised and recessed areas, the surface also maintains a high level of anti-abrasion resistance ensuring suitability to high-traffic applications whilst safeguarding the longevity of the product.

Details:

Our anti-slip glass is available in 8mm (on request) and 10mm (as standard) thickness with options in both transparent and semi-transparent formats. With potential for incorporation of colour, lighting and special effects finishes, design possibilities are completely flexible.

Suitable for both residential and commercial applications, Mega Glass has a range of options on offer to suit any vision with a choice of safety requirements possible to guarantee compliance across a range of installations.

Key Applications:

Airports, Stations, Museums, Offices, Hotels, Restaurants, Shopping Centres, Showrooms, Nightclubs and Residential Dwellings (Flooring & Rooflights)


Specification:

- UK processed toughened glass to BSEN12150
- Pendulum impact test rating of 1C1 under BSEN12600
- Glass can be fully processed, toughened & laminated
- Suitable for flooring & rooflight applications
- Can be back-lit
- Coating(s) with hydrophobic and oleophobic properties can be applied to allow water run-off and simplify the cleaning process




Lunaris-T on Low Iron (Transparent)

Stocked Thickness: 10mm
(Others available on enquiry)
Sheet sizes: 3210 x 2250mm
Rating: R10



Dots (Semi-Transparent)

Accessible Thickness: 10mm
(Others available on enquiry)
Sheet Size: 3210 x 2250mm
Minimum Rating: R10



Boxes (Semi-Transparent)

Accessible Thickness: 10mm
(Others available on enquiry)
Sheet Size: 3210 x 2250mm
Minimum Rating: R10



Lines (Semi-Transparent)

Accessible Thickness: 10mm
(Others available on enquiry)
Sheet Size: 3210 x 2250mm
Minimum Rating: R11