



## INTRODUCING A NEW HYBRID - THE PELI™ 9050

## AN INDUSTRY FIRST

The new 9050 is the next generation of Peli High Performance lighting.




The 9050 includes industry first technology

– The flexible "Dual Fuel" battery system
allows you to select between Rechargeable
Li-ion, AA alkaline or AA NiMH cells.


This class-leading LED also features dedicated full-time Flood or Spot modes, without the use of light-diminishing diffusers.

True differentiation between remote area task, and powerful search lighting is available in one compact and lightweight product, all at the touch of a button.



## VERSATILE ILLUMINATION

Switch between dedicated light Flood/Spot light modes to transform your 9050, providing up to 3369 Lumens – depending on the task and environment.



SPOT MODE:
489 METERS
2623 LUMENS

SPOT/FLOOD MODE:
417 METERS
3369 LUMENS

(Lumens and Beam Distance when using 2 x Li-Ion batteries)



SIMPLIFIED DOCKING

The 9050 features a quick-release charger base. A click sound verifies the fast & hassle free dismounting and re-mounting of the light.





FL1 STANDARDS SPECIFICATIONS	BATTERIES Li-lon	SPOT		FLOOD		SPOT/FLOOD	
		HIGH	LOW	HIGH	LOW	HIGH	LOW
LIGHT OUTPUT (Lumens)	2/3/4	2650	354	1119	291	3388	301
BEAM DISTANCE (Metres)	2/3/4	490	117	48	24	419	110
BEAM INTENSITY (Candelas)	2/3/4	59760	7846	577	149	43824	3011
RUN TIME (hours/mins)	2 3 4	4h 15m 7h 30m 9h 30m	13h 30m 20h 26h	5h 30m 8h 45m 12h	11h 16h 20h	2h 45m 4h 30m 6h	11h 16h 20h

Full Recharge Time: 2 batteries – 5h 30m, 3 batteries – 7h 30m, 4 batteries – 10h.



## Peli Products (UK) Ltd

Peli House, Peakdale Road, Brookfield, Glossop SK13 6LQ T: 01457 869999 E: sales@peliproducts.co.uk

©2022 Peli Products (UK) Ltd. All contents included should be considered as guidelines and only valid at the time of publication. All trademarks and logos displayed herein are registered and unregistered trademarks of Peli Products, S.L.U. and others.



















