




PORTABLE WORK LIGHT RANGE

ZERO - Noise | Emissions | Fuel Consumption



www.power-2go.com

TL-100 | SINGLE HEAD

PORTABLE LED WORK LIGHT



This ultra-portable LED work light delivers an impressive 4000 lumens from its adjustable lamp head, ensuring optimal visibility in any workspace. Lightweight yet durable, it's your perfect companion for on-the-go lighting needs.

Powerful Work Light Performance: Instant directional, bright, glare-free light

Adjustable Lamp Head: Tool-free adjustment for the perfect angle, a breeze to set up and operate

Extended Mast Height: Provides superior light distribution over a wide area

Rugged Construction: Built tough to withstand the rigors of daily use

Versatile Application: Workshops, garages, construction sites or outdoor events.

Product Code: PTG-TL-100	
Height:	0.9-1.4m
Net Weight:	3Kg*
Battery:	D24-100 x 1
Turbo Mode:	4h 15mins - 4000lm
Standard Mode:	8h 36mins - 2500lm
Balanced Mode:	16h 49mins - 1500lm
ECO Mode:	44h - 450lm

*excluding battery



TL-200DH | DUAL HEAD

PORTABLE LED WORK LIGHT

Crafted for contractors, job sites, and workshops, this powerhouse offers up to 12000* lumens, ensuring no corner stays dim. Its 360-degree rotation capability guarantees full coverage, while the tripod design keeps it steady wherever you work. Cordless and weatherproof (IP66).

Versatile Adjustability: With its dual heads and independent rotation capability

Rugged Durability: Heavy-duty aluminum housing and IP66 weatherproof rating

Adjustable Brightness: Optional Mains Power Pack

Dual Rainproof USB Outputs: Charge your devices on the go with dual rainproof USB outputs

Phone Stand Feature: Convenient phone stand feature for safe charging



Product Code: PTG-TL-200DH

Height:	1-2.3m
Net Weight:	6.3Kg*
Battery:	D24-100 x 1
AC Power:	X1-75-56BH Driver x 1 - 12000lm
Turbo Mode:	4h 15mins - 6000lm
Standard Mode:	8h 36mins - 3500lm
Balanced Mode:	16h 49mins - 2200lm
ECO Mode:	44h - 600lm

*excluding battery

TL-300 | DUAL HEAD

PORTABLE LED WORK LIGHT




An ideal lighting rig for engineers and maintenance crews working on larger sites, only 8.2kg*. With battery or mains power options, an impressive 14,000lm maximum light output and a 3.1m mast height, this durable, IP66 protected unit will illuminate work sites perfectly - indoors or out.

- Versatile Adjustability:** Dual heads and independent rotation capability
- Rugged Durability:** Heavy-duty aluminum housing and IP66 weatherproof rating
- Adjustable Brightness:** Up-to 14,000lm with the optional AC Mains Power Driver
- Dual Rainproof USB Outputs:** Charge your devices on the go with dual USB outputs
- Phone Stand Feature:** Convenient phone stand feature for safe charging

Product Code: PTG-TL-300	
Height:	1.25-3.1m
Net Weight:	8.2Kg*
Battery:	D24-100 x 2
AC Power:	X1-75-56BH Driver x 1 - 14000lm
Turbo Mode:	6h 30mins - 8000lm
Standard Mode:	13h 2mins - 5000lm
Balanced Mode:	26h 6mins - 3000lm
ECO Mode:	74h 22mins - 800lm

*excluding battery



TL-400 | DUAL HEAD

PORTABLE LED WORK LIGHT

Your ultimate work light solution for versatile and reliable lighting in any environment. This LED work light is meticulously designed to provide superior illumination coverage, long-lasting battery life, and exceptional convenience for various applications, from emergency infrastructure to construction sites.

- Speedy Deployment:** Single-latch tripod release mechanism, enabling quick setup
- Versatile Adjustability:** Self-locking pole with 360°+ adjustable lighting distribution
- One-Person Operation:** Dual handles enable easy transport and adjustment
- Weatherproof Design:** IP66 weatherproof rating, built to withstand the toughest conditions
- Durable and Versatile:** Weighing only 10.1kg*, 17000lm light output and 2.2 meter height

Product Code: PTG-TL-400	
Height:	0.65-2.2m
Net Weight:	10.1Kg*
Battery:	D24-100 x 3 D24-500 x 1
AC Power:	X1-75-56BH Driver x 1 - 17000lm
Turbo Mode:	10h 15h - 10000lm
Standard Mode:	20h 30h - 6300lm
Balanced Mode:	40h 60h - 3800lm
ECO Mode:	100h 150h - 1800lm

*excluding battery



TL-500-4.2 | QUAD HEAD

PORTABLE LED WORK LIGHT



Crafted with engineers and large scale maintenance crews in mind, it provides versatility and durability, creating the next generation of portable illumination.

Speedy Deployment: Hand held controller for easy deployment and operation

Versatile Adjustability: Electric telescopic pole with 360°+ fully adjustable lighting

Rugged Durability: Triple wheel + self-locking legs, adapts to all terrains

Weatherproof Design: IP65, resistant to 8-level winds, corrosion-resistant

Durable and Versatile: 51kg*, fits easily into standard SUVs for single-person loading.

Product Code: PTG-TL-500-4.2

Height:	1.23-4.2m
Net Weight:	51Kg*
Battery:	D24-500 x 3
AC Power:	P2G-X5-320 x 1 - 62000lm
Turbo Mode:	10h - 33000lm
Standard Mode:	18h - 17000lm
Balanced Mode:	39h - 9500lm
ECO Mode:	114h - 2800lm

*excluding battery



TL-500-5.3 | QUAD HEAD

PORTABLE LED WORK LIGHT

The tallest and most powerful unit in our range, delivering unmatched lighting capabilities, versatility, and durability, establishing a new benchmark for portable illumination.

Speedy Deployment: Hand held controller for easy deployment and operation

Versatile Adjustability: Electric telescopic pole with 360°+ fully adjustable lighting

Rugged Durability: Triple wheel + self-locking legs, adapts to all terrains

Weatherproof Design: IP65, resistant to 8-level winds, corrosion-resistant

Durable and Versatile: 51kg*, fits easily into standard SUVs for single-person loading.

Product Code: PTG-TL-500-5.3

Height:	1.31-5.3m
Net Weight:	54Kg*
Battery:	D24-500 x 3
AC Power:	P2G-X5-320 x 1 - 65000lm
Turbo Mode:	10h - 35000lm
Standard Mode:	18h - 18000lm
Balanced Mode:	39h - 10000lm
ECO Mode:	114h - 3000lm

*excluding battery



PL-200



PORTABLE LED WORK LIGHT

This innovative led work lighting tower features a unique petal design that provides 360-degree lighting from four lighting elements equipped with diffusers. Ensuring reduced glare with even distribution of light over a wide area.

Rugged Construction: Suitable for demanding work environments and outdoor events

Advanced Lighting Design: 360-degree lighting coverage, with four petal lighting elements

Long-lasting Performance: Over 8 hours (Standard - 45 Eco Mode) of continuous illumination

Dual Rainproof USB Outputs: Charge your devices on the go with dual rainproof USB outputs

Phone Stand Feature: Built-in phone stand feature for convenient safe charging.

Product Code: PTG-PL-200	
Height:	1.3-2.5m
Net Weight:	6.3Kg*
Battery:	D24-100 x 1
AC Power:	X1-75-56BH Driver x 1 - 12000lm
Turbo Mode:	4h 15mins - 6000lm
Standard Mode:	8h 36mins - 3500lm
Balanced Mode:	16h 49mins - 2200lm
ECO Mode:	44h - 600lm

*excluding battery



PL-300

PORTABLE LED WORK LIGHT

The PL-300 area lighting tower has a unique design that provides 360 degree lighting from 4 lighting elements equipped with diffusers. Provides reduced glare and an even distribution of light over a wide area.

Versatile Power Options: Accepts 2 x D24-series batteries and can also be powered by mains power when used with the optional external X1-75-56BH Mains Power Pack

Rugged Durability: Heavy-duty aluminum mast and IP66 weatherproof rating

Adjustable Brightness: 800lm - 8,000lm - battery | 14,000lm - optional Mains Driver

Portable and Easy to Deploy: Weighing just 8.8kg* and with a mast height of 3.4M

Phone Stand Feature: Convenient phone stand feature for safe charging

Product Code: PTG-PL-300	
Height:	1.6-3.4m
Net Weight:	8.8Kg*
Battery:	D24-100 x 2
AC Power:	X1-75-56BH Driver x 1 - 14000lm
Turbo Mode:	6h 30mins - 8000lm
Standard Mode:	13h 2mins - 5000lm
Balanced Mode:	26h 6mins - 3000lm
ECO Mode:	74h 22mins - 800lm

*excluding battery



PT-200 | Remote Control

PAN-TILT LED WORK LIGHT



The PT-200 Remote Control Pan-tilt Work Light is your go-to solution for professional-grade illumination. Boasting a powerful 12000 lumens, this battery powered, rechargeable LED flood light delivers unparalleled brightness wherever you need it.

Rugged Durability: IP66 ingress rated and IK10 impact rated, reliable performance in any environment

Flexible Mounting Options: The magnetic base, offers secure mounting to metallic surfaces, keeping the light exactly where you need it. Plus, added security with the provided safety

Remote Control Convenience: Features a handheld remote control with a 30-foot range, you can adjust the flood light precisely without needing to touch it.

Product Code: PTG-PT-200	
Height:	0.4m
Net Weight:	4.4Kg*
Battery:	D24-100 × 1
Turbo Mode:	2h 30mins - 12000lm
Standard Mode:	4h 20mins - 6500lm
ECO Mode:	19h - 1200lm

*excluding battery



PS-200

HIGH OUTPUT LED WORK LIGHT

This rugged lantern delivers unparalleled performance both indoors and out. With its IP66 ingress rating and IK10 impact rating, the PS-200 is built to withstand the toughest environments while providing reliable illumination where you need it most.

Long-Lasting Durability: 44 hrs of constant Eco operation at 600lm, reducing downtime and ensuring continuous productivity without the need for frequent battery changes

Powerful Illumination: 360-degree light output, ensuring every corner is brightly lit

Glare-Free Operation: Integrated diffuser, which eliminates glare, reducing eye strain

Seamless Battery Swapping: Ensure uninterrupted operation



Product Code: PTG-PS-200	
Height:	0.35m
Net Weight:	2Kg*
Battery:	D24-100 × 1
Turbo Mode:	4h 15mins - 6000lm
Standard Mode:	8h 36mins - 3500lm
Balanced Mode:	16h 49mins - 2200lm
ECO Mode:	44h - 600lm

*excluding battery

D24-100



LITHIUM-ION BATTERY PACK

With a capacity of 98Wh, this rechargeable battery pack ensures long-lasting performance, keeping you illuminated during extended work sessions indoors or outdoors.

Versatile Compatibility: Designed for seamless integration with our range of portable lighting equipment, ensuring reliable power whenever you need it

Convenient Charge Indicator: The built-in charge indicator feature lets you easily monitor the battery's power level, ensuring you're always prepared for your next task

Effortless Recharging: Compatible with our Single Dock Charger or Dual Bay Lithium Battery Pack Charger (sold separately), making recharging a simple and efficient process.

Product Code: PTG-D24-100

Rated Power:	98Wh
Rated Voltage:	24.5V
Rated Capacity:	4.0Ah
Working Temperature:	-10-50C
Working Humidity:	20-98%
Battery Cycle Life:	1000 times
Dimension:	113x102x101mm
Weight:	0.9kg



D24-500

LITHIUM-ION BATTERY PACK

Boasting a capacity of 490Wh, this rechargeable battery pack complements our larger lighting towers enabling them to operate for extended periods of time.

Convenient Charge Indicator: The built-in charge indicator feature lets you easily monitor the battery's power level, includes a warning flash when power is below 10%

Power Protection Switch: Allows the battery to be completely turned off preventing the possibility of accidental discharge

Integrated Handle: Makes swapping out and charging of the battery more convenient.



Product Code: PTG-D24-500

Rated Power:	490Wh
Rated Voltage:	24.5V
Rated Capacity:	20.0Ah
Working Temperature:	-10-50C
Working Humidity:	1-98%
Battery Cycle Life:	1000 times
Dimension:	313x109x101mm
Weight:	3.0kg

TKC-9-D24-100 | 9 Bay

BATTERY CHARGING CASE



Nine bay charger case for use with our D24-100 series batteries. Includes 9 x D24-100 batteries. Supplied with a UK plug and power lead. This portable case makes charging multiple batteries convenient and allows for several days off-grid operation.

Portability: Case includes collapsible extending handle and roller wheels

Charging Options: Suitable for power mains and solar panel input charging when off-grid

Charging Indicator: Indicator lights to show batteries are charging correctly

Status Display: Screen shows the status of charging throughout the full cycle

Charging Lead: Provided with a 3m input cable and UK plug.

Product Code: PTG-TKC-9-D24-100	
Input:	AC 100-240V (Solar Panel charging option)
Output:	29.2V 4.0A
Simultaneous Charging:	1-9Pcs D24-100
Charge Time:	50min (Single D24-100)
Working Temperature:	0-50C
Working Humidity:	T20-98%
Dimensions:	545mm x 406mm x261mm
Weight:	15.5kg (Case and 9Pcs D24-100)



TKC-9H | 3 Bay

BATTERY CHARGING CASE

Three bay charger case for use with our D24-500 series batteries. Includes 3 x D24-500 batteries. Supplied with a UK plug and power lead. This portable case makes charging multiple batteries convenient and allows for several days off-grid operation.

Portability: Case includes collapsible extending handle and roller wheels

Charging Options: Suitable for power mains and solar panel input charging when off-grid

Charging Indicator: Indicator lights to show batteries are charging correctly

Status Display: Screen shows the status of charging throughout the full cycle

Charging Lead: Provided with a 3m input cable and UK plug.

Product Code: PTG-TKC-9H	
Input:	AC 100-240V (Solar Panel charging option)
Output:	29.2V 4.0A
Simultaneous Charging:	1-3Pcs D24-500
Charge Time:	50min (Single D24-500)
Working Temperature:	0-50C
Working Humidity:	T20-98%
Dimensions:	545mm x 406mm x261mm
Weight:	15.5kg (Case and 9Pcs D24-100)



MC-1 Single Bay

LITHIUM BATTERY CHARGER



Designed for the Power-2Go D24 series batteries, our lithium battery pack chargers ensure rapid and reliable charging, so your equipment is always ready when you need it.

Rapid Charging: Complete a full charge in just 95 minutes, ensuring your equipment maintains optimal performance at all times.

Built for Safety: Features comprehensive protection against over-charge, over-discharge, over-current and short-circuit, safeguarding your batteries and equipment from damage.

Compact and Powerful: Despite their small footprint, these chargers packs a punch, delivering fast and reliable charging power without taking up valuable space.

Product Code: PTG-MC-1

Input:	AC 100-277V 1.5A
Output:	29.4V 1A
Charge Time:	95min - (Single D24-54)
Working Temperature:	0-40C
Working Humidity:	1-98%
Dimension:	135x90x65mm
Weight:	0.5kg



*not supplied with battery

MC-2 Dual Bay

LITHIUM BATTERY CHARGER

Our dual lithium battery pack chargers ensure rapid and reliable charging, completing a full charge in 100 just minutes.

Automatic Operation: Simply insert the battery and the charging process begins automatically, stopping when the battery reaches full capacity for hassle-free use.

Dual Bay Design: Focus on charging one or two of our D24 series lithium batteries at a time, delivering efficient power restoration exactly when you need it.

Rapid Charging: Complete a full charge in just 100 minutes, ensuring your equipment maintains optimal performance at all times.

Product Code: PTG-MC-2

Input:	AC 100-277V 1.5A
Output:	29.2V 2A
Charge Time:	100min - (Single D24-100)
Working Temperature:	0-50C
Working Humidity:	1-98%
Dimension:	251x154x153mm
Weight:	0.8kg



*not supplied with battery

X1-75-56BH



MAINS POWER SUPPLY DRIVER

Use this rugged power supply with our range of portable devices to gain maximum light output and to take advantage of the smooth dimming feature. Compatible with TL-200DH, TL-400DH, PL-200 and PL-300 devices. Supplied with UK plug and lead.

Optimal Brightnes: Mains connection lets you take advantage of the brightest light settings

Adjustable Dimmer: Easily alter the brightness of the light source with a simple dimmer dial

Charging Functionality: During use, the supply driver will also charge batteries fitted to the lighting unit

Secure fixing: Attached lanyard keeps the unit safe and secure.



Product Code: PTG-X1-75-56BH

Input:	100-277V-Max:0.8A 50/60Hz PF>0.95
Output:	36V 2.2Amp
Dimensions:	190x87x49mm
Weight:	0.9kg

P2G-X5-320

MAINS POWER SUPPLY DRIVER

Made to enhance the light output of our larger lighting towers while retaining the smooth dimming feature. Compatible with TL-500 devices. Supplied with UK plug and lead.

Optimal Brightnes: Mains connection lets you take advantage of the brightest light settings

Adjustable Dimmer: Easily alter the brightness of the light source with a simple dimmer dial

Charging Functionality: During use, the supply driver will also charge batteries fitted to the lighting unit



Product Code: P2G-X5-320

Input:	100-277V-Max:6A 50/60Hz PF>0.95
Output:	36V 7.2Amp - 24V 2A
Dimensions:	405x87x51mm
Weight:	2.8kg

PORTABLE LIGHT RANGE | KEY PARAMETERS



Model	PT-200 Remote Pan-tilt Light	PS-200 Site Light	TL-100 Portable Light Tower	TL-200 Portable Light Tower	PL-200 Petal Light Tower	TL-300 Portable Light Tower	PL-300 Petal Light Tower	TL-400 Portable Light Tower	TL-500-4.2m Light Tower	TL-500-5.3m Light Tower
Height	0.4m	0.35m	0.9-1.4m	1-2.3m	1.3-2.5m	1.25-3.1m	1.6-3.3m	0.65-2.2m	1.23-4.2m	1.31-5.3m
Net Weight	4.4Kg	2Kg	3Kg	6.3Kg	6.5Kg	8.2Kg	8.8Kg	10.1Kg	51Kg	54Kg
Battery	D24-100 ×1	D24-100 ×1	D24-100 ×1	D24-100 ×1	D24-100 ×1	D24-100 ×2	D24-100 ×2	D24-100 ×3 D24-500 ×1	D24-500 ×3	D24-500 ×3
Turbo Mode	2h30mins	4h15mins	4h15mins	4h15mins	4h15mins	6h30mins	6h30mins	10h 15h	10h	10h
	12000LM	6000LM	4000LM	6000LM	6000LM	8000LM	8000LM	10000LM	33000LM	35000LM
Standard Mode	4h20mins	8h36mins	8h36mins	8h36mins	8h36mins	13h2mins	13h2mins	20h 30h	18h	18h
	6500LM	3500LM	2500LM	3500LM	3500LM	5000LM	5000LM	6300LM	17000LM	18000LM
Balanced Mode		16h49mins	16h49mins	16h49mins	16h49mins	26h6mins	26h6mins	40h 60h	39h9mins	39h9mins
		2200LM	1500LM	2200LM	2200LM	3000LM	3000LM	3800LM	9500LM	10000LM
ECO Mode	19h	44h	44h	44h	44h	74h22mins	74h22mins	100h 150h	114h	114h
	1200LM	600LM	450LM	600LM	600LM	800LM	800LM	1800LM	2800LM	3000LM