BNVD-SG-E SINGLE GAIN NIGHT VISION BINOCULAR



NIGHT VISION DEVICES

SPECIFICATIONS

POWER SOURCE:	(1) AA-SIZE BATTERY
FOCUS RANGE:	9.8" TO INFINITY
OPERATION TIME:	20+ HRS, 1 ALKALINE BATTERY
	40+ HRS, 1 LITHIUM BATTERY
MAGNIFICATION:	ONE POWER (1X)
FIELD OF VIEW:	40°
DIOPTER ADJUSTMENT:	-6 TO +2
EYE RELIEF:	25MM
WEIGHT (W/O BATTERY):	560 G (19.8 OZ)
DIMENSIONS:	4.3″ X 4.2″ X 3.3″

FEATURES

- **TACTICAL MONOCULAR CUTOFF**
- **40+ HOUR BATTERY LIFE WITH** LITHIUM AA BATTERY
- SUBMERSIBLE TO 66 FT UP TO 3 HRS
- SINGLE GAIN CONTROL KNOB
- POWER OFF THE UNIT WHEN IN AN UPRIGHT POSITION AND POWER ON WHEN FLIPPED DOWN

The BNVD Binocular is a dual tube goggle with gain control. The BNVD-SG operates with a single gain control knob that controls both eyepieces simultaneously. Depending upon the amount of ambient light, the user can adjust the tube brightness (gain) lower to compensate for overly bright conditions or to increase the gain under extreme dark conditions. The BNVD-SG can be used as a monocular by choosing which side you want to use as your night vision eye and rotate the other side/arm of the binocular up and out of the way. This enhanced capability allows the user to rotate either monocular channel away from their eye while leaving the other monocular channel in place. This provides the operational flexibility to use the BNVD-SG as either a dual-eye or single-eye device. When used as a monocular, the user can operate the BNVD-SG with weapon mounted sighting equipment without sacrificing night-time situational awareness. Best of all with all the added features, the BNVD-SG is still substantially lighter than the AN/PVS single tube goggle!

BNVD-SG now features a "Tactical Monocular Cutoff", which turns off power to each channel of the binocular whenever a channel is rotated up out of the users' line of sight. This eliminates stray light emitting from the monocular eyepiece, which would reveal the user to anyone else on the battlefield. The BNVD-SG has an automatic system power cutoff whenever the BNVD-SG is flipped up into the helmet mounte stow position, and then powers back on when it is flipped back down. This feature can also be turned off via a four position ON/OFF switch. The BNVD-SG is submersible to 66 feet (20 meters) for up to 3 hours. The BNVD-SG is available with an optional battery pack, which holds 3 "AA" Alkaline batteries for run times exceeding 50 hours.

The BNVD-SG can be used with optional 3x Afocal Magnifiers. Each 3x Magnifier can be either slide onto each objective lens screw into the threads on the objective lenses. For extended use, it is recommended to screw them on to prevent the lenses from falling off. These magnifiers transform the BNVD-SG into a fixed 3X Magnification Binocular.

With our expansive capabilities and strategic partnerships, we are able to custom build any of our NVD manufactured products with image intensifiers from either Harris Corporation®, Photonis 4G® or L3®. This includes green and white phosphor and thin or un-filmed image tubes. This system complies with MIL-STD 810G, MIL-PRF-A3256342A(CR) and MIL-PREF-49427(CR).

INTL BNVD-SG-E DATA SHEET - REV - SEPTEMBER 2018 INTERNATIONAL@NVDEVICES.COM NVDEVICES.COM 610-395-9743



THOMAS Sole Authorised UK Distributor Thomas Jacks Limited, Apex House, Timothy's Bridge Road, Stratford-upon-Avon, Warwickshire, CV37 9BF t +44 (0)1789 264100 e info@thomasjacks.co.uk www.thomasjacks.co.uk

Specifications subject to change without notice. Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State Office of Defense Trade Controls prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130. Approved for public release under International Traffic in Arms Regulations (ITAR) 22CFR 120.11

BNVD-SG-E SINGLE GAIN NIGHT VISION BINOCULAR

HELMET MOUNT OPTIONS



The BNVD-SG can be used as a monocular by choosing which side you want to use as your night vision eye and rotate the other side/arm of the binocular up and out of the way. Each arm is tight enough so that the rotated arm will not fall down, but stay in its user adjusted position. To use as a binocular, rotate both sides down or when night vision is no longer needed, shut off and rotate both sides up and out of the way.

Never before could a binocular remain mounted when sighting with a rifle. The BNVD-SG does not need to be removed. Simply rotate one monocular of the BNVD-SG up and out of the way, so that the user can view through the dayscope & night vision weapon sight.

BNVD-SG WITH WEAPON SIGHT



STANDARD ACCESSORIES

Soft Carry Case, Demist Shields, Sacrificial Windows, IR Spot/Flood Lens, Dovetail Mounting Adapter, Lens Tissue, (2) AA Batteries, Operator's Manual & Card, Neck Cord, Eyecups and Retaining Lens Covers.

OPTIONAL ACCESSORIES

3X Magnifier, G24 Helmet Mount, Shuttered Eyeguards, Camera Adapter, and Battery pack for 50-60 hours of continual use for extended missions.



INTL BNVD-SG-E DATA SHEET - REV - SEPTEMBER 2018

NVDEVICES.COM » 610-395-9743 NINTERNATIONAL@NVDEVICES.COM



Sole Authorised UK Distributor Thomas Jacks Limited, Apex Ho Thomas Jacks Limited, Apex House, Timothy's Bridge Road, Stratford-upon-Avon, Warwickshire, CV37 9BF t +44 (0)1789 264100 e info@thomasjacks.co.uk www.thomasjacks.co.uk

Specifications subject to change without notice. Export of the commodities described herein is strictly prohibited without a valid export license issued by the U.S. Department of State Office of Defense Trade Controls prescribed in the International Traffic in Arms Regulation (ITAR), Title 22, Code of Federal Regulations, Parts 120-130. Approved for public release under International Traffic in Arms Regulations (ITAR) 22CFR 120.11