



DEPLOYED LOGIX
SHELTERS
THE FIRST IN THE FIELD

X-SERIES SHELTER SYSTEM

- **INFINITELY EXPANDABLE.**
- **LINKS UP EASILY WITH OTHER X-SERIES, X-HUBS, AND ASAP® SHELTERS.**
- **WEATHER-RESISTANT SYSTEM.**
- **SMALL FOOTPRINT, LARGE SQUARE FOOTAGE.**

At Deployed Logix we're redefining rapid deployment. Through our extensive work with law enforcement, search and rescue teams, various first responders, private organizations both domestically and abroad, and the military, our team understands that when a crisis calls, seconds count. Discover why we are the leader in American-made, rapidly deployable disaster preparedness products.

Specification and design may be altered without notice due to continuous product development. LAST UPDATED JUNE 2022.

Proudly made in the USA.
CAGE CODE: 7CFK2 | DUNS#: 079751064



X-SERIES SPECIFICATIONS

| MODEL NAME: | X-16 | X-24 | X-32 | X-40 |
|-----------------------------|---|--|--|--|
| DIMENSIONS (L X W X H): | 16.25 x 21.75 x 10 ft (4.95 x 6.63 x 3.05 m) | 24.27 x 21.75 x 10 ft (7.40 x 6.63 x 3.05 m) | 32.28 x 21.75 x 10 ft (9.84 x 6.63 x 3.05 m) | 40.31 x 21.75 x 10 ft (12.29 x 6.63 x 3.05 m) |
| USABLE SHELTER AREA: | 353.44 ft ² (32.84 m ²) | 527.87 ft ² (49.04 m ²) | 702.09 ft ² (65.23 m ²) | 876.74 ft ² (81.45 m ²) |
| FOOTPRINT AREA W/ STAKING: | 833.44 ft ² (77.43 m ²) | 1,088.07 ft ² (101.09 m ²) | 1,342.39 ft ² (124.71 m ²) | 1,597.34 ft ² (148.40 m ²) |
| DOORS: | 2 | 2 | 2 | 2 |
| WINDOWS (SIDE // ENDWALLS): | 4 // 4 | 6 // 4 | 8 // 4 | 10 // 4 |
| ECU DUCTS: | 4 sets | 4 sets | 4 sets | 6 sets |
| STOVE PIPE VENTS: | Optional | Optional | Optional | Optional |
| PERSONNEL REQUIRED: | 2 min // 4 preferred | 3 min // 4 preferred | 4 min // 6 preferred | 6 min // 8 preferred |
| SETUP TIME: | <10 minutes | <15 minutes | <20 minutes | <25 minutes |
| SNOW AND RAIN LOAD: | Snow: 10 lb/ft ² (48.82 kg/m ²) Rain: 2 in/hr (5.08 cm/hr) | | | |
| WIND RATING: | 65 mph, gusts 75 mph (104 kmh, gusts 120 kmh) | | | |
| TOTAL SYSTEM WEIGHT: | 485 lb (219.5 kg) | 750 lb (340.2 kg) | 895 lb (406 kg) | 1,073 lb (486.7 kg) |
| FRAME SECTION: | 3 total | 4 total | 5 total | 6 total |
| ROOF: | 1 total | 1 total | 1 total | 1 total |
| ENDWALL: | 2 total | 2 total | 2 total | 2 total |
| SIDEWALL: | 2 total | 2 total | 2 total | 2 total |

