



NICKELBACKS

SWEAT ABSORBING NITRILE GLOVES

SPEC SHEET

SPECIFICATIONS	
TENSILE STRENGTH (Min. Mpa)	3 SIZES (M,L,XL)
Before Aging : 15 Mpa	For a comfortable fit.
After Aging : 15 Mpa	LATEX FREE
ELASTICITY/ELONGATION (%)	Nitrile gloves are a latex free solution for professionals concerned with latex sensitivity.
Before Aging : 550%	
After Aging : 500%	
PROTEIN CONTENT	FULLY TEXTURED/MICRO-ROUGHENED
N/A	For a superior wet or dry grip.
AVG. MIN. POWDER MASS (Min. mg Per Glove) <2 mg	POWDER-FREE
AQL LEVEL : 1.5	Avoids interference with adhesives and inks.
SUPERB TENSILE STRENGTH Beaded cuff for increased tear resistance.	
ADVISORY: Clean washed for 75% less residue than typical nitrile gloves.	
50 individual gloves per box	

COLOR	
GRAY	
PART NUMBERS	
D07-08-009-050 (M)	
D07-08-010-050 (L)	
D07-08-011-050 (XL)	
UPC CODES	
D07-08-009-050 (M)	
EACH	781513657812
MASTER	70781513657811
D07-08-010-050 (L)	
EACH	781513657829
MASTER	70781513657828
D07-08-011-050 (XL)	
EACH	781513657836
MASTER	70781513657835
10 BOXES PER MASTER CASE	



THICKNESS



HIGH ABRASION



DriTek® Confort Technology:
Advanced flock lining is a soft cotton like nitrile glove lining that wicks away moisture for added confort in extended use.



EcoTek® Biodegradability Technology:
92.6% biodegradable in 2.5 years. ASTM D5526-12 test result do not predict future biodegradation.

100% Air Inspected.



**Prices and Quantities
Subject to Change**