

GENERAL

Water Resistance	IP66
Pan Angle	Continuous 360°
Tilt Angle	Straight downward to 45 degrees above horizontal
Body Material	Aluminum
Width	6.65 in / 169 mm
Depth	7.68 in / 195 mm
Height	7.8 in / 198 mm
Weight	94.5 oz / 2680 g
Operating Temperture Range	-4°F to 122°F -20°C to 50°C
Ports	1 TF card slot, 2 HDMI ports, 2 DC ports
Display Type	LCD
Screen Size	10.1 in

POWER

Power Supply	12V DC
Camera Amperage @12V DC	750mA
Display Amperage @12V DC	320mA
Adaptor Connection with both Camera and Display	1200mA

FEATURES

- · Variable Speed Remote Control
- Sleep Mode
- Return To Home Function
- · High Resolution 384x288 pix thermal imaging
- · Infinite 360° Panning
- Low Latency HDMI compatible Wired Screen
- · App Control on the Dark 30 App
- Versatile Mounting Options: (Permanent bolts, suction cups, or 45.3 kg / 100 lb pull magnets.)
- Water Resistant

SENSOR

**	T
Type of Sensor	Thermal sensor
Sensor Resolution	384x288 pix
Pixel Size	17 micron
Spectral Range	8 - 14 µm
Detector NETD (30Hz, 300K, F/1)	<40 mK
Color Palettes	5
Detection Range	1250 yds / 1150 m

OPTICS

Lens Material	Germanium
F/# NUMBER (lens)	1
Lens Diameter	30 mm
Focal Length	30 mm
Digital Zoom	1-8x
Magnification	n/a
Field of View Horizontal	12°
Field of View Vertical	9°
Field of View Diagonal	15°

ADDITIONAL ACCESSORIES

- 2 in Riser
- Base Kit
- Remote
- 10.1 in Screen

The D30 Defiance LT 384 PTZ enhances the capabilities of nocturnal hunters and law enforcement professionals who have previously had to use thermal handheld devices on foot and through vehicles, which obscured their views through windows and windshields. Mounted on top of a vehicle, the D30 Defiance offers a 360° field of view, allowing users to survey their surroundings with unparalleled clarity and precision. This elevated perspective not only provides a broader and clearer view but also enhances detection and target tracking without users needing to stop or dismount.



10.1 in SCREEN

Video Output	1920x1200 pix
Display Type	LCD
Screen Size	10.1 in
Weight	17 oz / 482 g
Brightness Setting	0-100
Power Supply	12V
Operating Temperature	-4°F to 158°F / -20°C to 70°C
Storage Temperature	-22°F to 176°F -30°C to 80°C
Connection	HDMI

SCREEN FEATURES

- · Adjustable Brightness Display
- · Off button to prevent night blindness
- · Direct unit connection via HDMI to minimize lag

2 in RISER

Weight	1.11 lb / 503 g
Dimensions	7.5 X 6.5 X 2 in 191 x 165 x 51 mm
Materials	Polycarbonate

RISER FEATURES

- Rugged easy to use
- Stackable
- · Included mounting hardware

BASE KIT

Weight	2 lb / 0.9 kg
Dimensions	7.5 X 6.5 in / 191 x 165 mm
Cable Length - HDMI	4 m
Cable Length - Power	4 m
Power	12V
Materials	Aluminum and Plastic
Power Supply	12V DC
External Power Supply	Car cigarette power, 12V DC

BASE KIT

- Multiple Cable Management Configuration
- Protective cover

REMOTE

Connection	Wireless
Power	2 AAA batteries

REMOTE

- · Wireless connection
- Innutive joystick operation
- · Ergonomic magnification toggle