



Improving quality of resuscitation





Why Quality of CPR is Important

Proper depth of chest compressions during CPR creates adequate blood flow and oxygen delivery to the heart and brain. Moreover, proper rate of chest compressions during CPR is an important determinant of return of spontaneous circulation (ROSC) and survival with good neurologic function.



- 1. Perform chest compressions to a depth of at least 5 cm (2 inches) but not greater than 6 cm (2.4 inches).
- 2. Perform chest compressions at a rate of 100 to 120 times/min.
- 3. Minimize interruptions in compressions.

Nihon Kohden's CPR-1100 CPR assist contributes to improved quality of resuscitation by analyzing the compressions and providing precise feedback about the CPR quality.

See and Hear the Quality of CPR

CPR assist shows the depth and tempo of chest compressions by LED and audio. This real-time feedback helps you adjust your compressions to perform higher quality CPR. It also supports easier CPR training.





Orange: tempo indicator Blue: good chest compression

Evaluate the Quality of CPR

CPR assist can communicate with a PC by Bluetooth connection.

For training, the real-time CPR waveform and measurement value can be shown on a PC with QP-110V viewer software for PC (included with CPR assist). This software scores the quality of CPR to assist in making helpful evaluations for the user's future CPR.



Defibrillation report, QP-551VK

CPR training report, QP-110V

Rescue data is stored in the CPR assist during CPR and the rescue data can be reviewed on a PC with optional QP-551VK defibrillation report viewer software.

Manage the Quality of CPR

CPR assist can also communicate with a Nihon Kohden defibrillator by Bluetooth connection.

The real-time CPR waveform and measurement values can be shown with other parameters such as ECG, SpO_2 , CO_2 and NIBP on the defibrillator screen.

All necessary information for rescue can be confirmed on one screen by using the CPR assist with a Nihon Kohden defibrillator.



Specifications

· ·		
[Dimensions	71 (W) × 32 (H) × 126 (D) mm
١	Weight	166 g (not including battery)
E	Battery operation time	5 hours continuous use
(Communication method	Bluetooth standard Ver 2.1 + EDR
3	Standard accessory	QP-110V CPR assist viewer software
1	Measurement items	Depth, tempo, tilt and sinking of patient's back

The Bluetooth word mark and logo are registered trademarks and are owned by the Bluetooth SIG, Inc.

This brochure may be revised or replaced by Nihon Kohden at any time without notice.



NIHON KOHDEN CORPORATION

1-31-4 Nishiochiai, Shinjuku-ku, Tokyo 161-8560, Japan Phone +81 (3) 5996-8036 Fax +81 (3) 5996-8100 www.nihonkohden.com