

Socomec

Breakers & Attachments



HILLHEAD 2026

DMS

Range



MODEL		DMS 50	DMS 95/2	DMS 165	DMS 210	DMS 300	DMS 400	DMS 530	DMS 980
Energy	joule	120	240	330	500	700	900	1080	1700
Frequency	c/min	1200	1200	1200	1200	1100	900	900	900
Oil flow	L/min	17/25	27/40	35/50	40/55	50/80	70/100	80/110	100/130
Pressure	bar	120	120	120	120	120	120	120	130
Weight	kg	60	95	165	210	300	400	530	1000
Tool diameter	mm	38	45	55	62	72	80	85	102
Height	mm	750	1000	1050	1200	1423	1455	1700	1830
Min. width	mm	125	130	165	190	205	225	235	280
Backpressure	bar	20/30	20/30	20/30	20/30	20/30	25	25	25

■ Ideal excavator-Equipment combination

DMS 50	0,7 - 1,2	DMS 95/2	1,4 - 1,8	DMS 165	2,2 - 2,8
DMS 210	3 - 4	DMS 300	4,5 - 6	DMS 400	7 - 8
DMS 530	8,5 - 10	DMS 980	11 - 14		

DMS

Range



MODEL		DMS 1350TS	DMS 1800TS	DMS 2400TS	DMS 3000TS	DMS 4000TS	MDO 6000TS
Energy	joule	2700	4700	6400	8400	10000	12000
Frequency	c/min	550/780	480/650	460/630	380/500	360/480	340/460
Oil flow	L/min	150	190	220	250	320	400
Pressure	bar	140	140	140	150	160	160
Weight	kg	1350	1800	2400	3000	4000	6000
Tool diameter	mm	120	135	152	165	180	198
Height	mm	2210	2346	2569	2861	3023	3352
Min. width	mm	246	390	430	478	560	605
Backpressure	bar	10	10	10	10	10	10

■ Ideal excavator-Equipment combination

DMS 1350TS

16 - 20

DMS 1800TS

22 - 28

DMS 2400TS

25 - 33

DMS 3000TS

31 - 45

DMS 4000TS

45 - 65

MDO 6000TS

60 - 90

RVS

Range



MODEL		RVS 2200	RVS 2800	RVS 3800	RVS 5300	RVS 7800
Weight	kg	2200	2800	4000	6000	8000
Operating pressure	bar	250	250	250	250	250
Oil Flow Rate	l/min	140	180	210	270	320
Frequency	rpm	1500	1500	1500	1500	1700

■ Ideal Excavator-Equipment Combination

RVS 2200

20 - 25

RVS 2800

23 - 29

RVS 3800

32 - 40

RVS 5300

42 - 60

RVS 7800

65 - 90