shindaiwa®

welder-generators

6 The Dell, Enterprise Drive,
Four Ashes, Wolverhampton
England, WV10 7DF
Phone: +44 (0) 1902 791855
Email: info@shindaiwa.co.uk

Eco400 Stage 5

			Generating Method	Rotating Field
Welding Generator	Operation		SINGLE	DUAL
	CC MODE	Rated Voltage (V)	35.2	28.0
		Current Adj Range (A)	30 - 380	50 - 200
		Welding Rod (mm)	2.0 - 8.0	2.0 - 4.0
		Gouging Rod (mm)	3.2 - 8.0	3.2 - 5.0
	CV MODE	Rated Voltage (V)	34.5	21.0
		Voltage Adj Range (V)	14 - 34.5	14 - 28
		Welding Wire (mm)	0.6 - 2.0	0.6 - 1.6
AC Generator	Rated Frequency (Hz)		50	
	Phase		1 - Phase	3 - Phase
	Rated Voltage (V)		110	415
	Power Factor		1.0	0.8
	Rated Output (kVA)		3.3	12
Engine	Make/Model		Kubota D902	
	Rated Speed (min^{-1})		3000	
	Fuel		Diesel	
	Fuel Tank Capacity (L)		43	
Set	Dimensions		Skid	Road Tow Trailer
	Length (mm)		1435	2710
	Width (mm)		700	1450
	Height (mm)		848	1270
	Dry Weight (kg)		474	555
	Noise (dB(A) @ 7m)		58	

- Dual Operator
- 415V & 110V
- Fully Bunded
- CC/CV Mode

Kubota STAGE V