

Cleanliness. Service. Outstanding quality.

An overview of our products.



mariner 

Equipment and technical specifications:



proliner
navi3



proliner
plus



proliner



proliner
natur



proliner
tube



clubliner
plus



clubliner

Equipment

	proliner navi3	proliner plus	proliner	proliner natur	proliner tube	clubliner plus	clubliner
Sensor high tech (HS)	•	optional	–	optional	optional	optional	–
Sensor Basic	optional	•	–	•	•	•	–
Without gyro	optional	–	•	optional	optional	–	•
Box for debris collection	•	•	•	•	–	•	•
Lamella filters 50/100/130 µm	6	6	6	6	–	2	2
Filter surface 6 m ²	•	optional	optional	optional	–	–	–
Filter surface 4,5 m ²	optional	•	•	•	–	–	–
Filter surface 1,2 m ²	–	–	–	–	–	•	•
Rotating brushes	•	–	–	–	–	–	–
Option to mount rubber brushes	•	•	•	•	•	•	•
Transport trolley	•	•	•	•	•	•	•
Cable drum	•	•	•	•	•	–	–
Floating cable length (m)	30/40/50/60	30/40/50/60	30/40/50/60	30/40/50	30/40	25/30	25/30
Power cable 10/20 m	•	•	•	•	•	•	•
Wireless transmitter	•	•	•	•	•	•	•

Technical specifications

Robot dimensions (L x W x H, cm)	83 x 61 x 52	55 x 60 x 37	55 x 60 x 37	78 x 60 x 37	55 x 60 x 50	44 x 43 x 29	44 x 43 x 29
Cleaning width (mm)	up to 700	up to 700	up to 700	up to 700	up to 700	up to 530	up to 530
Robot weight (kg)	43	28	28	38	37	16	16
Mains supply voltage 100-240 V, 50/60 Hz	•	•	•	•	–	•	•
Safety extra low voltage < 30 V DC	•	•	•	•	–	•	•
Pump capacity (L/min)	850	850	850	850	up to 400	500	500
Drive speed (m/min)	7.5-18	7.5-18	7.5-18	7.5-18	7.5-18	7.5-15	7.5-15
Frequency 868/433 MHz	•	•	•	•	•	•	•
Minimum water depth (cm)	20-30	20-30	20-30	20-30	20-30	20	20
Maximum water depth (m)	10*	10*	10*	10*	7	10*	10*

* 8-10 m only with restrictions



Automatic operations and functions:



Direction change

	on wall contact	•	•	•	•	•	•	•
	without wall contact	•	•	•	•	•	•	•
	Section cleaning	•	•	–	•	•	•	–
	on inclines	•	•	•	•	•	•	•
	at inclines	•	•	–	•	•	•	–
	for beach pools	•	•	–	•	–	•	–

Drive pattern

	Drive pattern N	•	•	–	•	•	•	–
	Drive pattern H	•	•	–	•	•	•	–
	Drive pattern X	•	•	•	•	•	•	•

Additional functions

	Bypassing of obstacles	•	•	–	•	•	•	–
	Immersion mechanism	•	optional	optional	optional	–	–	–
	Adjustment of the start time	•	•	•	•	•	•	•
	Switch-off	•	•	•	•	•	•	•
	Maximum cleaning time	•	•	•	•	•	•	•
	Automatic mode for pools with liner	•	•	•	•	•	•	•

Swiss Quality.

mariner-3s.com



Switzerland:
Mariner 3S AG
Brunnmattstr. 7
5236 Remigen
+41 56 297 8800
info@mariner-3s.com