



CCUS and Low Carbon Fuels

11 – 12 March 2025 | Tokyo, Japan

GHG EMISSION REDUCTION BY CONVERTING VENTING SYSTEM TO FLARING AT CENTRAL PROCESSING PLATFORM (CPP)

Dzulkarnain Muhamad





Outline



GHG Emissions Reduction Roadmap



CPP Vent to Flare Conversion Project





Estimated GHG Emissions Reduction



Q&A Session

GHG Emissions Reduction Roadmap






Problem Statement

- Existing CPP Vent System is emitting HC Gas (primarily Methane, CH₄) into the atmosphere
- CH₄ is 25 times more potent than CO₂ (100 years Global Warming Potential)

Objective


- To achieve GHG Emissions Reduction by converting CPP Vent System to Flare System

Project Timeline




Scope of Modification / Installation

- Replacement of Vent Tip to New Flare System – Combined HP LP flare tips
- Replacement of Existing CS Piping (DN 450 for HP, DN 200 for LP) to SS 316L Piping– 20m Spool (EL +76.630)
- Installation of New Flare Ignition Package
- Installation of New Pilot Line (DN 25) and Ignition Line (DN 25)
- Installation / Tie in from FG System and Utilities Air to New Flare Ignition Package
- Removal of Existing Vent Snuffing Package



Estimated GHG Emissions Reduction

GHG Emissions by System (2025-2040)



A total of 85% Emissions Reduction in GHG Emissions (Vent System) until EOFL



Note:

1. Emissions for 2025-2028 is based on forecasted production data (WPB) – only affected source are shown.
2. EOFL based on MR#2/3 Approved Production Profile
3. Assume GHG emissions reduction/ flaring system online starting from Q3 2025
4. Assume yearly Emissions for 2029-2040 same as per emissions in 2028